

Socket Box Timers

- Ideal for most heating applications
- Timer 'on' status indicator
- Fits a 25mm dual appliance socket box should you require to mount the timer next to a fused spur or socket outlet
- Will fit directly to any 25mm deep socket box fitted with an earth terminal
- T108A-C is suitable for discharge lighting applications
- All products are clammed for ease of display



Technical Data

Voltage 230V AC, 16A resistive load, 2A inductive load (T108A-C 8A inductive)
 Conforms to IEC 60730-1, IEC 60730-2-7
 KEMA-KEUR BS Certification mark - BS EN 60730-2-7:2010

Part No	Description	Dimensions	
Mechanical Timers			
T100A-C	24hr Mechanical Timer 96 on/off settings Analogue clock face On/timed/off switch selector	H77 x W72 x D43mm (Plate 86 x 86mm)	
T101A-C	7 Day Mechanical Timer 84 on/off settings (12 per day) Analogue clock face On/timed/off switch selector Minute hand indicator		
Electronic Timers			
T105A-C	7 Day Electronic Timer with 150hr battery backup 24 on/off programmes Digital display Manual override Summer time setting option Countdown timer function and 'Random' setting	H77 x W72 x D43mm (Plate 86 x 86mm)	
T108A-C	7 Day Electronic Timer as above with increased 8A inductive rating Digital display Manual override Summer time setting option and 'Random' setting		