

Immersion and Dual Tariff Timers

- Timer 'on' status indicator
- All products are clammed for ease of display



Technical Data

Voltage 230V AC 50Hz, 16A resistive load, 2A inductive load
 Conforms to BS EN 60730-1 and BS EN 60730-2-7
 KEMA-KEUR BS Certification mark - BS EN 60730-2-7:2010 (Except T109-C)

T109-C: -

The KingShield Dual Tariff Boost Timer controls the use of off-peak cheap rate electricity. It can be surface mounted and has easy to set time segments.

	Part No	Description	Product Information/ Dimensions
Mechanical Timers			
	T102A-C	24hr Mechanical Timer 96 on/off settings	Analogue clockface On/timed/off switch selector H127 x W74 x D48mm
	T103A-C	24hr Mechanical Timer with 24hr battery backup 96 on/off settings	Analogue clockface On/timed/switch selector H127 x W74 x D48mm
	T104A-C	7 Day Mechanical Timer 84 on/off settings (12 per day)	Analogue clockface On/timed/off switch selector Minute hand indicator H127 x W74 x D48mm
Electronic Timers			
	T106A-C	7 Day/24hr Electronic Timer with 150hr battery backup 24 on/off programmes	Digital Display Manual Override Summer time setting Countdown timer function and 'Random' setting H127 x W74 x D48mm
Dual Tariff Boost Timer			
	T109-C	16A Dual Tariff Boost Timer	15 - 120 minute boost facility Anti-tamper timer cover H85 x W155 x D50mm