

Incoming Rating up to 250A Outgoing Rating up to 160A

Outgoing MCCB



3 Pole Moulded Case Circuit Breaker

Adjustable Thermal Trip (0.63 to 1 x In)

16kA and 25kA Option

Poles	Connection Type	Current Rating	Adjustable Thermal	16kA Icu Code	25kA Icu Code
3 Pole	Cage	25	16-25	1L025CA3	1N025CA3
		40	25-40	1L040CA3	1N040CA3
		63	40-63	1L063CA3	1N063CA3
		80	50-80	1L080CA3	1N080CA3
		100	63-100	1L100CA3	1N100CA3
		125	80-125	1L125CA3	1N125CA3
		160	100-160	1L160CA3	1N160CA3



Single Pole Moulded Case Circuit Breaker - Fixed Magnetic and Fixed Thermal

Poles	Connection Type	Current Rating	25kA Icu Code
1 Pole	Cage	16	0N016CF1
		20	0N020CF1
		25	0N025CF1
		32	0N032CF1
		40	0N040CF1
		50	0N050CF1
		63	0N063CF1
		80	0N080CF1
		100	0N100CF1
		125	0N125CF1



Accessories	Code
Wide terminal shroud for incoming cable connection to MCCB 3 pole frame 2	ASW3PF20
Wide terminal shroud for incoming cable connection to MCCB 4 pole frame 2	ASW4PF20
Long busbar shroud incoming MCCB to busbar assembly 3 pole	ASL3PF20
Long busbar shroud Incoming MCCB to busbar assembly 4 pole	ASL4PL20
Long terminal shroud for outgoing MCCB 3 pole	ASL3PF10
Long terminal cover for outgoing single pole MCCB	ASL1PF00
Single pole blank module (1 module per part number) 3 required for 3P	ABM1PF10
Auxiliary contact change over switch 1C/O	AAUXLF12
Alarm auxiliary contact left 1C/O	AALMLF12
Shunt trip 200VAC-240VAC	AST240ACF12
Under voltage trip 200VAC - 240VAC	AUV240ACF12
Barrel key lock for door with 2 keys (same key code)	SBLK2
Shroud lock for Frame 1 and Frame 2 shrouds	ASLCK12
Toggle lock for Incomer and outgoing MCCB's	ACBTLK12
4 pole replacement incoming shroud MCCB to busbar	ASINC4PF20

