

### 13 Amp Fused Connection Units

- Manufactured to BS 1363 part 4
- Angled colour coded terminals with captive screws
- Minimum mounting box depth 35mm
- Terminal capacity 3 x 2.5mm<sup>2</sup>, 2 x 4.0mm<sup>2</sup> & 1 x 6.0mm<sup>2</sup>



SBS52

Brushed Steel	Description	Inner Carton	Outer Carton
SBS52	Switched with power indicator	5	50
SBS54	Unswitched with power indicator	5	50

### 45 Amp Double Pole Switches

- Manufactured to BS 4177 and BS EN 60669-1
- Cooker Control Units manufactured to BS4177, Double Pole Switches to BS EN 60669-1
- Minimum mounting box depth 47mm
- L & N terminal capacity 4 x 4.0mm<sup>2</sup>, 3 x 6.0mm<sup>2</sup> & 1 x 16.0mm



SBS70G

Brushed Steel	Description	Inner Carton	Outer Carton
SBS70G	Switched with 13 Amp socket and power indicator	5	50
SBS72	Switched with power indicator, double plate	5	50
SBS74	Switched with power indicator, single plate	10	100

### Dimmer Switch – Leading Edge, Push Type

- Manufactured to BS EN 60669-2-1
- Minimum mounting box depth 25mm
- 10mm spacer available to provide additional wiring space (817 – Sq, 818 – Rectangle)
- Suitable for compact fluorescent lamps (CFL) and LED Dimming
- There can be issues with dimming CFL and LED lamps at a low lighting level. The Nexus dimmer products have an adjustable minimum level feature which can be used to adjust the lighting output at a low level, to stabilise the load.




SBS81P

Brushed Steel	Description	Inner Carton	Outer Carton
SBS81P	Single, 2 way, 400W	5	50
SBS82P	Double, 2 way, 400W	5	50

### Dimmer Switch – Intelligent Trailing Edge, Push Type

- Intelligent trailing edge dimmer suitable for LED, halogen, CFL and incandescent lamps
- Soft start, smooth dimming control and silent operation
- 2 Way push on/off with rotary control
- Overload protection
- Clearly marked terminals with backed out captive screws for easy installation
- Terminal capacity 3 x 1mm<sup>2</sup>, 2 x 1.5mm<sup>2</sup> & 1 x 2.5mm<sup>2</sup>
- Manufactured to BS EN 60669-2-1
- Minimum mounting box depth 25mm
- 200-250V AC



SBS81

Brushed Steel	Description	Inner Carton	Outer Carton
SBS81	Single, 2 way, push on/off (20-200W/5-100W LED)	5	50
SBS82	Double, 2 way, push on/off (20-200W/5-100W LED)	5	50

### 13 Amp Floor Socket Outlets

- With spring hinged cover
- Manufactured to BS 1363 part 2
- Twin earth fitted as standard to allow a double earth facility for installations requiring high integrity protective connection Ref. BS 7671:2008
- Minimum mounting box depth 25mm
- Terminal capacity 3 x 2.5mm<sup>2</sup>, 3 x 4.0mm<sup>2</sup> & 2 x 6.0mm<sup>2</sup>



SBS23G/FR




SBS24G/FR

Product Code	Description	Inner Carton	Outer Carton
SBS23G/FR	Single	10	100
SBS24G/FR	Double	5	50

### Co-Axial Sockets

- Minimum mounting box depth 25mm
- Manufactured to BS 5733
- Used for TV or FM co-axial aerial connection
- Screw terminal



SBS60

Brushed Steel	Description	Inner Carton	Outer Carton
SBS60	Co-axial socket, single	5	50


- See our Euro Module range for further Telecom, Data and Co-axial Options



APPROVED

### Telephone Outlets

- Minimum mounting box depth 35mm
- Manufactured to BS 6312



SBSBTM1

Brushed Steel	Description	Inner Carton	Outer Carton
SBSBTM1	Telephone master, single	5	50
SBSBTS1	Telephone secondary, single	5	50

- See our Euro Module range for further Telecom, Data and Co-axial Options



APPROVED

### Shaver Socket

- Manufactured to BS EN 61558-1 and BS EN 61558-2-5
- Terminal capacity 3 x 2.5mm<sup>2</sup> & 2 x 4.0mm<sup>2</sup>
- Minimum mounting box depth 47mm



SBS20G

Brushed Steel	Description	Inner Carton	Outer Carton
SBS20G	Shaver socket 115/240V dual voltage	5	30

APPROVED