

HE8320 • HE7426

Screenzone double door air curtains



- Wall mounting bracket supplied for ease of installation and angular adjustment.
- Suspended, wall or trunking mounted.
- Fitted with integral switches.
- Optional remote switch HE8407 available.
- 2 heat settings HE7426, 3 heat settings HE8320.
- Fan only setting for air circulation.
- Automatic safety cut-out for thermal overload protection.
- Finished in white.

| Model No. | kW | Height x Depth x Width (mm) | Weight (kg) | Max. Mounting Height (m) | dBA |
|-----------|-----|-----------------------------|-------------|--------------------------|-----|
| HE8320 | 4.5 | 210 x 115 x 1040 | 8.8 | 2.3 | 49 |
| HE7426 | 6 | 210 x 115 x 1040 | 8.8 | 2.3 | 49 |

Note: 200mm clearance from ceiling required.

HE8326 • HE7433

Screenzone tall double door air curtains



- Wall mounting bracket supplied for ease of installation and angular adjustment.
- Suspended, wall or trunking mounted.
- Supplied with remote switch HE8408.
- 2 heat settings, 2 fan speeds.
- Fan only setting for air circulation.
- Automatic safety cut-out.
- Single/3 phase.
- Finished in white.

| Model No. | kW | Height x Depth x Width (mm) | Weight (kg) | Max. Mounting Height (m) | dBA |
|-----------|----|-----------------------------|-------------|--------------------------|-----|
| HE8326 | 6 | 210 x 115 x 1040 | 10.3 | 2.8 | 55 |
| HE7433 | 9 | 210 x 115 x 1040 | 10.3 | 2.8 | 55 |

Note: 200mm clearance from ceiling required.

CA1309S - CA1516S

Screenzone 1300MM & 1500MM Extra wide air curtains



- Single/3 phase on CA13 models.
- 3 phase only on CA15 models.
- Suspended, wall or trunking mounted.
- Wall mounting brackets supplied for optional use and ease of installation.
- Supplied with remote switch HE8408.
- 2 heat settings, 2 fan speeds.
- Multiple heaters can be controlled from one switch.
- Fan only setting for air circulation.
- Automatic safety cut-out for thermal overload protection.
- Finished in white.

| Model No. | kW | Height x Depth x Width (mm) | Weight (kg) | Max. Mounting Height (m) | dBA |
|-----------|----|-----------------------------|-------------|--------------------------|-----|
| CA1309S | 9 | 276 x 199 x 1305 | 20 | 3.4 | 52 |
| CA1312S | 12 | 276 x 199 x 1305 | 20 | 3.4 | 52 |
| CA1509S | 9 | 276 x 199 x 1530 | 22 | 3.4 | 52 |
| CA1512S | 12 | 276 x 199 x 1530 | 22 | 3.4 | 52 |
| CA1514S | 14 | 276 x 199 x 1530 | 22 | 3.4 | 52 |
| CA1516S | 16 | 276 x 199 x 1530 | 22 | 3.4 | 52 |

Note: 300mm clearance from ceiling required.

Explore more at www.consortepl.com