

Luminaire Support Connector

- The 6A plug-in ceiling rose offers a pluggable connection for luminaires
- The luminaire can be connected and disconnected under load
- Plug and sockets have 4 terminations for live, neutral, earth and loop-in
- Supports up to 5kg load
- Moulded in durable PC matt plastic material
- Cables have prepared ends



LSCPLG



LSC4PA



LSC4PA/4C3

Product Code	Description	Inner Carton	Outer Carton
LSC4PA/4C2	Luminaire support connector 4 pin plug + socket 2M 4C 0.75mm cable	10	100
LSC4PA/4C3	Luminaire support connector 4 pin plug + socket 3M 4C 0.75mm cable	10	100
LSC4PA	Luminaire support connector 4 pin plug + socket assembly	10	100
LSCPLG/RD	Luminaire support connector 4 pin plug – red	10	100
LSCPLG	Luminaire support connector 4 pin plug	10	100

Fluorescent Starters

- Manufactured to BS EN 60155
- All starters are kite marked



FS2



FS125

Product Code	Description	Inner Carton	Outer Carton
FSU	4-80 Watt	10	100
FS2	4-22 Watt single series	10	100
FS125	70, 75, 80, 85, 100-125 Watt	10	100

Fluorescent Starter Specifications

Lamp Type	Wattage	Circuit	FSU	FS125	FS2
150mm	4 W	Single	220/250V	-	110/130V
-	-	Twin Series	-	-	220/250V
225mm	6W	Single	220/250V	-	110/130V
-	-	Twin Series	-	-	220/250V
300mm	8W	Single	220/250V	-	110/130V
-	-	Twin Series	-	-	220/250V
525mm	13W	Single	220/250V	-	-
450mm	15W	Single	220/250V	-	110/130V
-	-	Twin Series	-	-	220/250V
360mm	16W	Single	220/250V	-	110/130V
600mm	18/20W	Single	220/250V	-	110/130V
-	-	Twin Series	-	-	220/250V
Circline	22W	Single	220/250V	-	110/130V
900mm	30W	Single	220/250V	-	-
Circline	32W	Single	220/250V	-	-
600mm	40W	Single	220/250V	-	-
1200mm	36/40W	Single	220/250V	-	-
1500mm	85/80W	Single	220/250V	240/250V	-
1800mm	70/85W	Single	220/250V	240/250V	-
2400mm	100/125W	Single	-	240/250V	-