

Plate Switches

- All plate switches are X-rated and can be used for switching inductive or fluorescent loads without de-rating
- Clear terminal markings
- Captive and backed out terminals (except SD1246 & SD1247)
- Only one size 4mm screwdriver needed
- Terminals have large lead-ins
- In compliance with BS EN 60669-1
- 25-year guarantee

10 Amp

Chrome/Stainless Steel

SD1203CH 1 gang 2-way
SD1203SS

SD1204CH 2 gang 2-way
SD1204SS

SD1205CH 3 gang 2-way
SD1205SS

SD1244CH 4 gang 2-way
SD1244SS

SD1246CH Intermediate
SD1246SS

SD1247CH 3 pole fan isolator
SD1247SS

Back Boxes

minimum recommended depth

	flush 25mm	dry lining 35mm
1g-3g	DB162	DB2540
4g	DB163	DB2541



SD1203SSW



SD1204SSW



SD1205SSB



SD1244SSW



SD1246CHB



SD1247SSW

Dimmer Switches

- Universal dimmers suitable for use with dimmable LED lamps (requiring leading or trailing edge control), incandescent lamps or low voltage lamps
- Suitable for loads up to 100W LED, 250W incandescent
- Clear terminal markings
- Push on / push off dimmers are suitable for 2-way circuits
- Spare dimmer knobs available
- In compliance with BS EN 60669-2-1, BS55014-1, BS 55014-2
- 2-year guarantee

Universal Dimmers

Chrome/Stainless Steel

SD1261CH 1 gang 2-way
SD1261SS

SD1262CH 2 gang 2-way
SD1262SS

Back Boxes

minimum recommended depth

	flush 35mm	dry lining 35mm
1g	DB164	DB2540



SD1261CH



SD1262SS

Chrome and Stainless Steel finish available with either black or white inserts.

When ordering, please indicate preference by adding suffix B or W at the end of the catalogue number.