

Ceiling Accessories

Ceiling Switches

6 AMP
SURFACE

WITHOUT
MOUNTING BLOCKS
FLUSH

50A
FLUSH

Mounting Blocks and Cords



- K3191WHI**
6A SP ONE-WAY
1.5M WHITE CORD WITH
WHITE ACORN
- K3191D1WHI**
6A SP ONE-WAY
2M WHITE CORD
AND 1X GRAPHITE BANGLE
- K3192WHI**
6A SP TWO-WAY
1.5M WHITE CORD
AND WHITE ACORN
- K3192D1WHI**
6A SP TWO-WAY
2M WHITE CORD
AND 1X GRAPHITE BANGLE

Supplied with mounting blocks.
Earth terminal is riveted in base of
mounting blocks.
BANGLE DIAMETER
50mm
These switches do not have to be
derated when used with fluorescent or
inductive loads.
FIXING CENTRES
50.8mm
BS EN 60669-1:1999

- 5 3190RCWHI**
6A SP TWO WAY
2M RED CORD WITH RED ACORN
PULL TO MAKE OR PULL TO
BREAK (MOMENTARY SWITCH
ACTION)
 - 5 3190RCD1WHI**
6A SP TWO-WAY
3M RED CORD
AND 2X RED BANGLE
- Supplied with mounting blocks.
BANGLE DIAMETER
50mm
BS EN 60669-1:1999

- 5 K3131WHI**
6A SP TWO-WAY
 - 5 3151WHI**
16A DP ONE-WAY
- Mounting blocks are not supplied. Use
K2051WHI or K2056WHI.
Suitable for installation in small circular
conduit boxes to BS EN 61386-1:2008
See page 354.
Ceiling switch cords are 1.5m minimum
length.
These switches do not have to be
derated when used with fluorescent or
inductive loads.
FIXING CENTRES
50.8mm
BS EN 60669-1:1999

- 5 3164WHI**
50A DP ONE-WAY
WITH NEON
1.5M WHITE
- 5 8329SSWHID1T9**
2M WHITE CORD WITH JOINT
UNION AND GRAPHITE BANGLE

MOUNTING BOXES
Surface Moulded
2140WHI, 2180WHI
2031WHI (extra wiring space)
Flush Steel
877ZIC (for full load applications)
Surface Metal
2211ALM, 2213ALM
Fitted with a mechanical 'OFF' indicator.
The switch fully complies with the
requirements within BS 7671 IET Wiring
Regulations with respect to safety
isolation for maintenance purposes
and provides a full 3mm contact gap
when 'OFF'.
DIMENSIONS
86 x 86mm
BANGLE DIAMETER
50mm
FIXING CENTRES
60.3mm
BS EN 60669-1:1999

- 5 K2051WHI**
10 MOUNTING BLOCK
FOR 6A OR 16A
SWITCHES
 - 5 K2056WHI**
5 MOUNTING BLOCK
WITH NEON
FOR 6A OR 16A
SWITCHES
 - 5 8329SSWHIT9**
10 1.5M WHITE CEILING
SWITCH CORD COMPLETE
WITH ACORN AND ONE PIECE
JOINT UNION
 - 9420SST9**
1 2M RED CEILING SWITCH
CORD COMPLETE WITH TWO
RED ACORNS AND ONE PIECE
JOINT UNION
 - 10 9420SSD1**
10 3M RED CEILING SWITCH CORD
COMPLETE WITH 2 X RED
BANGLES AND JOINT UNION
- K2051WHI and K2056WHI**
Earth terminal riveted in base.
DIAMETER
76mm not including Neon Lens
FIXING CENTRES
50.8mm
BS EN 60669-1:1999