



MAGDUOSH D

FlexiPoint Detector for Fire Detection

- 7 modes of fire detection including combined smoke/heat
- Built-in End of Line function
- Self-calibration every 6 hours
- Continuous dust contamination monitoring
- Device wiring base included



MAGDUOSH DS

FlexiPoint Detector with Sounder for Fire Detection

- 7 modes of fire detection including combined smoke/heat
- Complete with 3 sounder modes
- Built-in End of Line function
- Self-calibration every 6 hours
- Device wiring base included
- Continuous dust contamination monitoring



MAGDUOSH DSS

FlexiPoint Detector with Sounder & Strobe for Fire Detection

- 7 modes of fire detection including combined smoke/heat
- Complete with 3 sounder modes and LED strobe
- Built-in End of Line function
- Self-calibration every 6 hours
- Device wiring base included
- Continuous dust contamination monitoring

7 Modes Of Detection

Smoke 1 - Standard optical with high thermal enhancement

Smoke 2 - Standard optical with normal thermal enhancement

Smoke 3 - Low sensitivity optical with transient rejection

Heat 1 - Rate of Rise 58°C, general use in normal, stable environments (Class A1)

Heat 2 - Low fixed 58°C, Domestic kitchens etc (Class A1)

Heat 3 - Hi Fixed 90°C, Commercial kitchens, boiler rooms

Combined - Smoke 2 / Heat 2