



Grey Kits

White Kits

Please add colour to the code. G=Grey, W=White. e.g. SHDV4KD4G1TB

SHDV4KD2G

4 Channel Full HD 500GB CCTV System



- Complete with DVR, Cameras, Cable & System Power Supply
- 2 x 4MP HD day/night dome Cameras - SHDVC36FDG/SHDVC36FDW
- Hard drive options: SHDV4KD - 500GB, 1TB, 2TB, 4TB or 8TB
- 4 Channel System (Supports up to 4 cameras)
- 4 Megapixel live view and recording
- Recording options – Continuous / Scheduled / Motion
- Remote view via ESP[®] HDview APP for smartphones
- USB back up of recordings for easy evidence transfer
- Video outputs HDMI / VGA for connection to a monitor
- Premium Surveillance Hard Drive pre-installed
- Programmable Spot Output
- CMS software included for remote viewing via a pc
- Remote monitoring via wired connection or Wi-Fi (requires DVRWLA)
- Mouse driven comprehensive user interface
- Silent DVR operation

System

Main Processor	Embedded Processor
Operating System	Embedded LINUX

Video & Audio

Video Input	SHDV4KD - 4 channel BNC SHDV8KD - 8 channel BNC
Audio Input	SHDV4KD - 4 channel RCA SHDV8KD - 4 channel RCA
Audio Output	1 channel RCA

Display

Video Output	1 x HDMI, 1 x VGA, 1 x Auxiliary
Display Split	SHDV4KD - 1 and 4 SHDV8KD - 1, 4 and 10
Resolution	1024 x 768, 1280 x 720, 1280 x 1024, 1440 x 900, 1920 x 1080, 2560 x 1440

Recording

Video/Audio Compression	H.264 Mainprofile/G.711A
Resolution	4 Megapixel
Record Rate (Main Stream)	SHDV4KD - 4ch 4MP recording SHDV8KD - 8ch 4MP recording
Recording Mode	Manual/Motion Detection/Schedule

Playback & Backup

Sync Playback	SHDV4KD - 4ch 4MP recording SHDV8KD - 8ch 4MP recording
Backup Mode	Network/USB2.0 devices

Network

Ethernet	RJ45 10M/100M
Network Functions	HTTP, IPV4/IPV6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP
Network Monitoring	Web browsers, CMS, Android & iPhone apps

Storage

Internal HDD	1 SATA HDD, up to 8TB per HDD
--------------	-------------------------------

Auxiliary Interface

USB Interface	2
---------------	---

General

Power Supply	DC12V/2A
Power Consumption	<10W (without hard disk)
Operation Condition	0°C – +55°C / 10% – 90%
Dimensions	250(W)x230(D)x45(H)mm