



**MAGDUO2 Grey    MAGDUO2B Black**  
2 Zone Two Wire Fire Panel



- Two Wire fire alarm system
- Active end of line monitoring and head removal
- Up to 32 devices per zone (Dependent on Device Loading Unit: DLU)
- 4 line x 20 character LCD display
- Ability to differentiate between smoke detector, heat detector or a manual call point alarms
- Alarm confirmation feature
- Event log storing up to 500 events
- 3 enhanced test modes
- Zone can be configured to day/ night detection mode
- Delay programming options
- Certified to EN54 2/4 Standards
- Requires 2 x 12V 3.2Ah batteries (BAT32)
- Optional extended battery box with capacity for 2 x 12V 7.0Ah batteries

**Inputs**

Max Detectors Per Zone	Up to 32 Devices (Dependant on Device Loading Units , 160 per Zone)
------------------------	---------------------------------------------------------------------

**Power**


Mains Supply	230VAC, +10%, -15%, 50/60Hz
Operating Voltage	24vDC (Range 21-31vDC)
Standby Supply	2 x 12V 3.2Ah S.L.A Battery

**Outputs**

Zone	Up to 2 (300mA)
Monitored Sounder Circuits	Up to 2 (250 mA)
Monitored Relay Circuits	Up to 2 (250 mA)
Auxiliary Output	24vDC (300mA)

**Environment**

Working Temperature	5°C to 40°C
Dimensions	333 x 333 x 99mm
Weight	2.25 Kg



**MAGDUOBBB**  
Battery Expansion Box for MAGDUO



**MAGDUOPK** (Pack of 2)  
Two Wire Fire Panel Spare Key



**MAGDUOPCPS**  
MAGDUO Software