

- Two-wire connection
- Durable/Weatherproof door station
- Clear 2 Way audio
- Lock release option
- Wiring distance up to 100 meters
- Easy DIY installation

Handset

Input range	DC12V
Output power	<=0.6W
Working current	<=50mA
Dimension	215mm x 85mm x 60mm

Call Point

Input range	DC12V
Output power	<=0.6W
Working current	<=50mA
IP rating	55
Dimension	150mm x 65mm x 50mm



Audio Door Entry System **APKITA0**
 Additional APKITAOH Audio Handset **APKITA0H**

- Easy install, simple self-contained programming
- Up to 1,010 key tag holders or Pin numbers
- 2 separate user groups
- 2 relay outputs
- Anti tamper option
- Weather/dust proof robust construction IP65
- Complete with 10 tags

EZT3T10 Additional Proximity Tags (10 Pack)



Capacity	Zone 1 : 1000 Card/ Tag Combination Zone 2 : 10 Card/ Tag Combination
Reader Frequency	125KHz
Effective Distance	<5CM
Status Indication	Red / Green LED
Relay Operation	NO/NC: 4A@30vDC
Relay Duration	01-99sec
Working Temp.	-10 ~ +55 °C
Ingress Protection	IP65
Construction	Aluminium
Voltage	DC: 12V-24V AC: 12V-24V
Working Current	<120mA
Standby Current	<90mA
Dimensions	150(H)x43(W)x23(D)



Silver **EZTAG3** Black **EZTAG3B**
 Proximity and Keypad Door Entry