



Technical Hotline
+44 (0)1268 563720

Ancillary Products

Terminal Blocks



913WHI



914WHI

913WHI

3 WAY

914WHI

4 WAY

TERMINAL CAPACITY

913

Each terminal accepts up to 3 x 2.5mm² (solid conductors) or 3 x 4mm² (stranded conductors).

914

Each terminal accepts up to 4 x 1.5mm² conductors.

FIXING CENTRES

60.3mm for mounting on 'spare' lugs of 4 or 6 lug BS 4662 boxes.

Service Connector Boxes



1100BLK



1101BLK

5

1100BLK

5 WAY DOUBLE POLE
100A

5

1101BLK

5 WAY SINGLE POLE
100A

TERMINAL CAPACITY

All 35mm²

Where it is necessary to take the outer sheath of a double insulated cable into the box, the cable sizes are restricted to 16mm².

DIMENSIONS (OVERALL)

1100BLK 110 x 70 x 60mm

1101BLK 65 x 50 x 38mm

BS 7657:2010

Accessories For Boxes



3714



3710



800ZIC



3840ZIC

10

3714

BRASS EARTH TERMINAL WITH BRACKET

10

K3716

BRASS EARTH TERMINAL

3710

EXTENSION STUD

M3.5

ZINC-PLATED STEEL

OVERALL LENGTH 34MM

800ZIC

BOX FIXING FLANGE

USE TWO TO MOUNT ANY FLUSH MK BOX IN A DRY-PARTITION WALL

3840ZIC

CONVERSION BRACKET

COMPLETE WITH EARTH TERMINAL.

CONVERTS 25MM DEEP FLUSH SWITCH BOXES WITH 42MM FIXING CENTRES TO ACCOMMODATE PLATESWITCHES WITH 60.3MM FIXING CENTRES

100

5144SS000T9

LAMP LEAD AND RESISTOR ASSEMBLY FOR CEILING SWITCH BLOCKS AND 32A DP SWITCHES

100

100

1727OSS

LAMP LEAD AND RESISTOR ASSEMBLY TAG ENDED NEON FOR USE WITH 45A, 50A SWITCHES AND COOKER CONTROL UNITS

20

7179PS

LAMP LEAD AND RESISTOR ASSEMBLY, MALE CONNECTOR FOR SWITCHSOCKETS

10

1

10

10