



**SHDVCDBLG** Large Grey Camera Deep Base  
**SHDVCDBLW** Large White Camera Deep Base

**SHDVC550VFBG** Grey 5-50mm Lens 4MP HD Camera  
**SHDVC550VFBW** White 5-50mm Lens 4MP HD Camera



- 5 to 50mm Varifocal Lens
- High Definition 4MP AHD sensor
- Built in 50m Infrared LED Illumination
- Viewing Angle 42.1~ 6.3°
- D-WDR incorporating ATR
- 2D and 3D Noise Reduction
- Exposure Control
- High Light Compensation
- 3-Axis Cable Management Bracket
- IP66 Weatherproof Bullet Housing in Metal

|                         |  |
|-------------------------|--|
| Sensor Size             | 1/3"   |
| Effective Pixels        | NTSC/ PAL:2560(H)x1440(V)                        |
| Resolution              | 4 MP (2688 x 1520)                               |
| Minimum Illumination    | 0.1 Lux  |
| Scanning System         | Progressive                                      |
| Auto Electronic Shutter | NTSC: 1/60s-1/100,000s,<br>PAL: 1/50s-1/100,000s |
| IR Distance             | 50 Meters  |
| Video Output            | 1Vpp, 75 ohms                                    |
| Auto Gain Control       | Auto   |
| Power/Current           | DC12V(+/-10%)/720mA                              |
| Lens                    | 5-50mm Manual Zoom                               |
| Dimension               | Ø104 x 276 (L) mm inc. Bracket                   |
| Weight                  | 1190g  |
| Storage Temperature     | -30 ~ +60 °C RH95% Max                           |
| Operating Temperature   | -10 ~ +50 °C RH95% Max                           |



**SHDVCDBLG** Large Grey Camera Deep Base  
**SHDVCDBLW** Large White Camera Deep Base

**SHDVC622VFBG** Grey 6-22mm Lens 4MP HD Camera  
**SHDVC622VFBW** White 6-22mm Lens 4MP HD Camera



- 6 to 22mm Varifocal Lens
- High Definition 4MP AHD sensor
- Built in 50m Infrared LED Illumination
- Viewing Angle 37.2~ 14.4°
- D-WDR incorporating ATR
- 2D and 3D Noise Reduction
- Exposure Control
- High Light Compensation
- 3-Axis Cable Management Bracket
- IP66 Weatherproof Bullet Housing in Metal

|                         |  |
|-------------------------|--|
| Sensor Size             | 1/3"   |
| Effective Pixels        | NTSC/ PAL:2560(H)x1440(V)                        |
| Resolution              | 4 MP (2688 x 1520)                               |
| Minimum Illumination    | 0.1 Lux  |
| Scanning System         | Progressive                                      |
| Auto Electronic Shutter | NTSC: 1/60s-1/100,000s,<br>PAL: 1/50s-1/100,000s |
| IR Distance             | 50 Meters  |
| Video Output            | 1Vpp, 75 ohms                                    |
| Auto Gain Control       | Auto   |
| Power/Current           | DC12V(+/-10%)/720mA                              |
| Lens                    | 6-22mm Manual Zoom                               |
| Dimension               | Ø104 x 276 (L) mm inc. Bracket                   |
| Weight                  | 1190g  |
| Storage Temperature     | -30 ~ +60 °C RH95% Max                           |
| Operating Temperature   | -10 ~ +50 °C RH95% Max                           |