

- Waterproof IP55 metal multiway outdoor station
- High resolution colour Camera
- Built in keypad for door calling and code unlocking
- Simple 2 core cable installation
- Supports up to 32 apartments (Address Numbers 1-32)

|                    |                            |
|--------------------|----------------------------|
| Image Sensor       | 1/3" Colour CCD            |
| Min. Illumination  | 0.1 LUX                    |
| Illumination       | 6 LEDs                     |
| Lens               | 3.6mm                      |
| Viewing Angle      | 70°                        |
| Capacity           | 32 ID                      |
| Status Indication  | Audio                      |
| Relay Operation    | NO/NC                      |
| Working Temp.      | -20°C ~ +40°C              |
| Ingress Protection | IP55                       |
| Construction       | Aluminium                  |
| Voltage            | 24VDC                      |
| Dimensions         | 87mm(W)x 200mm(H)x 53mm(D) |
| Weight             | 640g                       |



**APDSKPFMS**  
Flush Mount Kit

MultiWay Video Door Station **APDSMW**  
MultiWay Video Door Station with Custom Apartment Addresses **SP1APDSMW**

- Waterproof IP55 metal multiway outdoor station
- High resolution colour camera
- Simple 2 core cable installation
- Supports up to 32 apartments ( Address Numbers 1-32)
- Capacitive keypad for apartment calling, proximity & code unlocking
- Complete with 10 pre-registered user tags
- 10,000 user tags supported

**EZT3ST10 Additional Proximity Tags (10 Pack)**



|                    |                            |
|--------------------|----------------------------|
| Image Sensor       | 1/3" Colour CCD            |
| Min. Illumination  | 0.1 LUX                    |
| Illumination       | 6 LEDs                     |
| Lens               | 3.6mm                      |
| Viewing Angle      | 70°                        |
| Capacity           | 32 ID<br>10,000 Tags       |
| Reader Frequency   | 125KHz                     |
| Effective Distance | <5CM                       |
| Status Indication  | Audio                      |
| Relay Operation    | NO/NC                      |
| Working Temp.      | -20°C ~ +40°C              |
| Ingress Protection | IP55                       |
| Construction       | Aluminium                  |
| Voltage            | 24VDC                      |
| Dimensions         | 87mm(W)x 200mm(H)x 53mm(D) |
| Weight             | 640g                       |



**APDSPXMW**  
Flush Mount Kit

MultiWay Video Door Station **APDSPXMW**  
MultiWay Video Door Station with Custom Apartment Addresses **SP1APDSPXMW**