

Spring connection with tension clamp technology (Z-Series)

Feed-through terminal blocks

ZDUB 2.5-2/2AN/TS15

2.5 mm²

Two connections



Width/Height/Depth	mm
max. current / max. cond. cross-section	A/mm ²
Max. clamping range	mm ²

5.1 x 33.5 x 31
30 / 4
0.13...4



Technical data

Rated data	
Rated voltage	V
Rated current	A
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Stripping length / Blade size	mm/-
Note	

Ordering data

Version	
	dark beige
	Blue
	Orange
Note	

Accessories

Plug-in cross-connection	
	2-pole
	10-pole
	2-pole
End plate / Partition plate	
	dark beige
	Blue
	orange
End bracket	
	beige
Screwdriver	
	Standard
Marking tags	

For detailed information on other accessories and application in the online catalogue


ZDUB 2.5-2/4AN/TS15

2.5 mm²

Four connections



10.2 x 33.5 x 31
30 / 4
0.13...4



IEC 60947-1	Ex eb II C Gb	Ex eb II C Gb	II 2 G D
IEC	UL	CSA	EN 60079-7
800	600	600	550
24	20	25	21
2.5	AWG 26...12	AWG 26...12	2.5 mm ²
8 kV / 3			
A2 / V-0			
DEMKO16ATEX1808U			
Rated connection			
0.5...4			
0.5...2.5 / 0.5...1.5			
10 / 0.6 x 3.5 mm			
Note			
TS 15 - block construction			

Type	Qty.	Order No.
ZDUB 2.5-2/4AN/15	100	1712780000
ZDUB 2.5-2/4AN/15 BL	100	1712790000
ZDUB 2.5-2/4AN/15 OR	100	1712800000

Type	Qty.	Order No.
ZDUB 2.5-2	24 A	1677120000
ZAP ZDUB	50	1704750000
ZAP ZDUB BL	50	1704760000
ZAP ZDUB OR	50	1704770000
ZEW 15	20	7920340000
SDIS SLIM 0.6X3.5X100	1	2749610000
DEK 5/5 MC NE WS	1000	1609801044
WS 10/5 MC NE WS	720	1635000000
DEK 5/5 MM WS	800	2007110000

The terminal blocks are cross-connected when using the ZQB 2.5 (1677120000).

ZDUA 2.5-2

2.5 mm²

Two connections



5.1 x 35 x 30
30 / 4
0.13...4



Ex eb II
C Gb II 2 G D

IEC 60947-7-1

IEC	UL	CSA	EN 60079-7
500	600	600	352
24	20	20	20
2.5	AWG 26...12	AWG 26...12	4 mm ²

6 kV / 3

A2 / V-0



DEMKO16ATEX1808U

Rated connection

0.5...2.5 / 0.5...2.5

0.5...2.5 / 0.5...2.5

10 / 0.6 x 3.5 mm

TS 15 - sliced construction

Type	Qty.	Order No.
ZDUA 2.5-2	100	1720920000
ZDUA 2.5-2 BL	100	1720930000
ZDUA 2.5-2 OR	100	1720940000

Type	Qty.	Order No.
ZQV 2.5N/2	24 A 60	1527540000
ZQV 2.5N/10	24 A 20	1527690000
ZAP/TW ZDUA	50	1720960000
ZAP/TW ZDUA BL	50	1720970000
ZAP/TW ZDUA OR	50	1720980000
ZEW 15	20	7920340000
SDIS SLIM 0.6X3.5X100	1	2749610000
DEK 5/5 MC NE WS	1000	1609801044
WS 10/5 MC NE WS	720	1635000000
DEK 5/5 MM WS	800	2007110000


ZDUA 2.5-2N

2.5 mm²

Two connections



5.1 x 42.5 x 35
30 / 4
0.13...4



IEC 60947-7-1

IEC	UL	CSA	EN 60079-7
800	600	600	
24	20	20	
2.5	AWG 26...12	AWG 26...12	

8 kV / 3

A2 / V-0



Rated connection

0.5...2.5 / 0.5...2.5

0.5...2.5 / 0.5...2.5

10 / 0.6 x 3.5 mm

TS 15 - sliced construction

Type	Qty.	Order No.
ZDUA 2.5-2N	100	1808200000

Type	Qty.	Order No.
ZQV 2.5N/2	24 A 60	1527540000
ZQV 2.5N/10	24 A 20	1527690000
ZAP/TW ZDUA2.5-2N	50	1808170000
ZEW 15	20	7920340000
SDIS SLIM 0.6X3.5X100	1	2749610000
DEK 5/5 MC NE WS	1000	1609801044
WS 10/5 MC NE WS	720	1635000000
DEK 5/5 MM WS	800	2007110000

