

ZDUB 2.5-2/2AN/DM

2.5 mm²

Two connections



Width/Height/Depth	mm
max. current / max. cond. cross-section	A/mm ²
Max. clamping range	mm ²

5.1 x 33.5 x 24	
30 / 4	
0.13...4	

Technical data

Rated data	
Rated voltage	V
Rated current	A
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Stripping length / Blade size	mm/-
Note	

Ordering data

Version	
End terminals	
	dark beige
	Blue
	yellow
Central terminals	
	dark beige
	Blue
	yellow
	orange
Note	

Accessories

Plug-in cross-connection	
	2-pole
End plate / Partition plate	
	dark beige
	Blue
	orange
Mounting blocks	
	dark beige
Screwdriver	
	Standard
Mounting foot for TS15 & TS35	
	dark beige
Marking tags	

For detailed information on other accessories and application in the online catalogue

ZDUB 2.5-2/4AN/DM

2.5 mm²

Four connections



10.2 x 33.5 x 24	
30 / 4	
0.13...4	

Rated data	
Rated voltage	V
Rated current	A
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Stripping length / Blade size	mm/-
Note	

Ordering data

Type	Qty.	Order No.
ZDUB 2.5-2/4AN/DB	100	1704690000
ZDUB 2.5-2/4AN/DB BL	100	1704700000
ZDUB 2.5-2/4AN/DB GE	100	1704720000
ZDUB 2.5-2/4AN/DM	100	1704540000
ZDUB 2.5-2/4AN/DM BL	100	1704550000
ZDUB 2.5-2/4AN/DM GE	100	1704570000
ZDUB 2.5-2/4AN/DM OR	100	1704560000

Type	Qty.	Order No.
ZDB 2.5-2	24 A	1677120000
ZAP ZDUB	50	1704750000
ZAP ZDUB BL	50	1704760000
ZAP ZDUB OR	50	1704770000
ZBB ZDUB	50	1704740000
SDIS SLIM 0.6X3.5X100	1	2749610000
MOFU 15/35 ZDUB	50	1723660000
DEK 5/5 MC NE WS	1000	1609801044
WS 10/5 MC NE WS	720	1635000000