


Screw connection with clamping yoke technology (W-Series)
PE terminal blocks

WPE 4N 4 mm²
Compact design



Width/Height/Depth	mm
max. current / max. cond. cross-section	-/mm ²
Max. clamping range	mm ²

6.1 x 50 x 37	
/ 6	
0.13...6	

Technical data

Rated data	
for wire cross-section	mm ²
Rated voltage to adjoining terminal	V
Rated impulse withstand voltage to adjacent terminal	kV
Rated short-time current	
Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Tightening torque / Clamping screw	Nm
Tightening torque for fixing screw	
Stripping length / Blade size	mm
Note	

Ordering data

Version	green/yellow
Note	

Accessories

End plate / Partition plate	dark beige
End bracket	dark beige dark beige, screwable
Screwdriver	Standard
Marking tags	
PEN bridge	

For detailed information on other accessories and application in the online catalogue

WPE 6 6 mm²



7.9 x 56 x 46.5	
/ 10	
0.08...10	

IEC 60947-7-2 Ex eb II C Gb II 2 G D

IEC	UL	CSA	EN 60079-7
6	AWG 20...8	AWG 20...8	6 mm ²
800			
8			
	720 A (6 mm ²)		
	3		
	A5 / V-0		
Approvals			
Rated connection			
0.5...10 / 1.5...10			
0.5...10 / 0.5...6			
0.8...1.3 / (M 3)			
0.5...1.0 Nm			
12 / 4.0 x 0.8 mm			
Note			

Type	Qty.	Order No.
WPE 6	50	1010200000
Note		

Type	Qty.	Order No.
WAP WDU2.5N/4N	50	1060000000
WEW 35/2	50	1061200000
SDS 0.8X4.0X100	1	2749360000
DEK 5/8 MC NE WS	800	1856740000
WS 8/6 MM WS	600	2007160000
DEK 5/6 MM WS	600	2007120000
Note		

For detailed information on other accessories and application in the online catalogue