

Screw connection with clamping yoke technology (W-Series)
Fuse terminal blocks

SAKS 5/35 DB


16 mm²

D 02 fuse E 18



Width/Height/Depth	mm
max. current / max. cond. cross-section	A/mm ²
Max. clamping range	mm ²

28 x 80 x 65
63 / 16
1.5...16



Technical data

Rated data	
Rated voltage to adjoining terminal	V
Rated current	A
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Tightening torque / Clamping screw	Nm
Blade size	

Note

IEC 60947-7-3

IEC	UL	CSA	EN 60079-7
400	600 (C)	600 (C)	
63	40	63	
16	AWG 14...6	AWG 14...6	
6 kV / 3			
V-0, 5VA			

CE ENEC TUV SÜD

Rated connection	
1.5...16 / 1.5...16	
1.5...16	
1.2...2.4 / (M 4)	
1.0 x 5.5 mm	

Ordering data

Version
500 V AC/DC, without LED
Note

Type	Qty.	Order No.
SAKS 5/35 DB	20	0502100000

Accessories

Screwable cross-connection	
	2-pole
	10-pole
	Lock washer
Mounting screw	
	Mounting screw
End plate / Partition plate	
	dark beige
Screw cover cap	
	SK
Safety fuses	

Gauge rings

Marking tags

Type	Qty.	Order No.
QL 2 SAKS2	36 A 20	0207800000
QL 10 SAKS2	36 A 20	0338900000
SS M4 D 128-A 4	100	0136400000
BFSC M4X9T	100	0103300000
WTW EN	20	1058800000
SK E18 SAKS5	20	0359310000
E 18/20A BL	20 A 10	0361300000
E 18/25A GE	25 A 10	0361400000
E 18/35A SW	35 A 10	0361500000
P 18/20 D02 BL SAKS5	20 A 50	0361800000
P 18/25 D02 GE SAKS5	25 A 50	0361900000
P 18/35 D02 SW SAKS5	35 A 50	0362000000
P 18/50 D02 WS SAKS5	50 A 50	0362100000
DEK 5/5 MC NE WS	1000	1609801044

For detailed information on other accessories and application in the online catalogue