

Screw connection with clamping yoke technology (W-Series)



Feed-through terminal blocks

Universal range

A

WDU 6 6 mm²

WDU 6 HV 6 mm²



Width/Height/Depth	mm
max. current / max. cond. cross-section	A/mm ²
Max. clamping range	mm ²

7.9 x 60 x 46.5	
57 / 10	
0.22...10	

7.9 x 60 x 46.5	
57 / 10	
0.22...10	

Technical data

Rated data	
Rated voltage	V
Rated current	A
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Tightening torque / Clamping screw	Nm
Stripping length / Blade size	mm/-
2 conductors with same cross-section (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Note	

IEC 60947-7-1 Ex eb II C Gb II 2 G D

IEC	UL	CSA	EN 60079-7
800	600	600	690
41	50	50	41
6	AWG 22...8	AWG 22...8	6 mm ²
8 kV / 3			
A5 / V-0			
Rated connection		Further connection	
0.5...10 / 1.5...10			
0.5...10 / 0.5...6			
0.8...1.6 / (M 3.5)			
12 / 0.8 x 4.0 mm			
0.5...2.5			
0.5...2.5 / 0.5...2.5			

IEC 60947-7-1

IEC	UL	CSA	EN 60079-7
1000			
41			
6			
8 kV / 3			
A5 / V-0			
Rated connection		Further connection	
0.5...10 / 1.5...10			
0.5...10 / 0.5...6			
0.8...1.6 / (M 3.5)			
12 / 0.8 x 4.0 mm			
0.5...2.5			
0.5...2.5 / 0.5...2.5			

Ordering data

Version	
	dark beige
	dark beige
	Blue
Note	

Type	Qty.	Order No.
WDU 6	100	1020200000
WDU 6 BL	100	1020280000

Type	Qty.	Order No.
WDU 6 HV	100	1412970000
WDU 6 IR	100	1393350000

Accessories

Screwable cross-connection	
	2-pole
	10-pole
End plate / Partition plate	
	dark beige
	dark beige
	Blue
	Blue
End bracket	
	dark beige
Testing / Checking	
	Standard
Cover	
	Blank, yellow
	Blank, white
Hak. Cable lugs	
Marking tags	
	DEK 5/8 MC NE WS
	WS 12/6.5 MC NE WS
	WS 8/8 MM WS
	DEK 5/8 MM WS
Plug-in cross-connection	
	2-pole
	10-pole
For detailed information on other accessories and application in the online catalogue	

Type	Qty.	Order No.
WQV 6/2	57 A 50	1052360000
WQV 6/10	57 A 20	1052260000
WAP 2.5-10	50	1050000000
WAP 16+35 WTW 2.5-10	20	1050100000
WAP 2.5-10 BL	50	1050080000
WAP 16+35 WTW 2.5-10 BL	20	1050180000
WEW 35/2	50	1061200000
WTA 3 WDU4	6 A 25	1632350000
WAD 8 MC NE GE	48	1112950000
WAD 8 MC NE WS	48	1112940000
DEK 5/8 MC NE WS	800	1856740000
WS 12/6.5 MC NE WS	540	1609920000
WS 8/8 MM WS	500	2007170000
DEK 5/8 MM WS	500	2007130000

Type	Qty.	Order No.
WQV 6/2	57 A 50	1052360000
WQV 6/10	57 A 20	1052260000
WAP 2.5-10	50	1050000000
WAP 16+35 WTW 2.5-10	20	1050100000
WAP 2.5-10 BL	50	1050080000
WAP 16+35 WTW 2.5-10 BL	20	1050180000
WEW 35/2	50	1061200000
WTA 3 WDU4	6 A 25	1632350000
WAD 8 MC NE GE	48	1112950000
WAD 8 MC NE WS	48	1112940000
DEK 5/8 MC NE WS	800	1856740000
WS 12/8 PLUS MC NE WS	420	1906000000
WS 8/8 MM WS	500	2007170000
DEK 5/8 MM WS	500	2007130000