


## Screw connection with clamping yoke technology (W-Series)

### Fuse terminal blocks

**WTR 4 SI SL**


**4 mm<sup>2</sup>**

With fuse holder



Width/Height/Depth	mm
max. current / max. cond. cross-section	A/mm <sup>2</sup>
Max. clamping range	mm <sup>2</sup>

6.1 x 61.5 x 97  
**6.3 / 6**  
**0.22...6**



#### Technical data

Rated data	
Rated voltage to adjoining terminal	V
Rated current	A
for wire cross-section	mm <sup>2</sup>
Rated impulse withstand voltage / Pollution severity	
UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm <sup>2</sup>
Flexible / Flexible with ferrule	mm <sup>2</sup>
Tightening torque / Clamping screw	Nm
Blade size	

IEC 60947-7-1

IEC	UL	CSA	EN 60079-7
400	300 (D)	300 (D)	
6.3	6.3	6.3	
4	AWG 22...10	AWG 22...10	
6 kV / 3			
V-0			

CE

Rated connection	
Solid / Stranded	mm <sup>2</sup>
Flexible / Flexible with ferrule	mm <sup>2</sup>
Tightening torque / Clamping screw	Nm
Blade size	

**Note**

#### Ordering data

Version	
	400 V AC/DC, without LED
Note	

Type	Qty.	Order No.
WTR 4 SI SL	25	<b>7910330000</b>

#### Accessories

Plug-in cross-connection	
	2-pole
	10-pole
End plate / Partition plate	
	dark beige
	Black
	dark beige
G-fuse cartridge, 5 x 20 mm (IEC 60127-2)	
	0.25 A fast
	0.50 A fast
	1.00 A fast
	2.00 A fast
End bracket	
	dark beige
Hak. Cable lugs	
Marking tags	

Type	Qty.	Order No.
ZQV 4N/2	32 A 60	<b>1527930000</b>
ZQV 4N/10	32 A 20	<b>1528090000</b>
<b>WAP 2.5-10</b>		
WAP 2.5-10	50	<b>1050000000</b>
WAP 2.5-10 SW	50	<b>1050010000</b>
WAP 16*35 WTW 2.5-10	20	<b>1050100000</b>
<b>G 20/0.25A/F</b>		
G 20/0.25A/F	0.25 A 10	<b>0430500000</b>
<b>G 20/0.50A/F</b>		
G 20/0.50A/F	0.5 A 10	<b>0430600000</b>
<b>G 20/1.00A/F</b>		
G 20/1.00A/F	1 A 10	<b>0430700000</b>
<b>G 20/2.00A/F</b>		
G 20/2.00A/F	2 A 10	<b>0430900000</b>
<b>WEW 35/2</b>		
WEW 35/2	50	<b>1061200000</b>
<b>HBT 1,5 - 3,0 RT</b>		
HBT 1,5 - 3,0 RT	100	<b>1312440000</b>
<b>HBT 2,5 - 3,0 BL</b>		
HBT 2,5 - 3,0 BL	100	<b>1312450000</b>
<b>DEK 5/6 MC NE WS</b>		
DEK 5/6 MC NE WS	1000	<b>1609820000</b>
<b>WS 12/6 MC NE WS</b>		
WS 12/6 MC NE WS	600	<b>1609900000</b>
<b>DEK 5/6 MM WS</b>		
DEK 5/6 MM WS	600	<b>2007120000</b>

For detailed information on other accessories and application in the online catalogue

