


ZTTR 2.5

2.5 mm²



Width/Height/Depth	mm
max. current / max. cond. cross-section	A/mm ²
Max. clamping range	mm ²

5.1 x 87 x 36
18 / 4
0.13...4



IEC 61984, In accordance with IEC 60947-7-1

Technical data

Rated data	
Rated voltage	V
Max. voltage of clamp support & pluggable system	-
Rated current	A
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Stripping length / Blade size	mm/-

IEC	UL	CSA	EN 60079-7
400	600	300	
16	16	16	
2.5	AWG 26...12	AWG 26...12	
	6 kV / 3		
	A2 / V-0		

CE RoHS REACH

Rated connection	Plug-in connection
0.5...4	
0.5...4 / 0.5...2.5	
10 / 0.6 x 3.5 mm	

Note

Ordering data

Version
dark beige
without isolator, dark beige
Note

Type	Qty.	Order No.
ZTTR 2.5	50	1865510000
ZTTR 2.5 0.TNHE	50	1905470000

Accessories

Plug-in cross-connection
2-pole
10-pole
End plate / Partition plate
dark beige
End bracket
dark beige
Screwdriver
Standard
Testing / Checking
Test plug
Holder for cartridge fuse 5 x 20 mm
400 V AC/DC, without LED
10 - 36 V AC/DC, red LED
140 - 250 V AC/DC, red LED
Module connector (max, 250 V)
without fittings
with wire jumper
With 1N4007 diode
Disconnect plug
removable, as replacement for release lever
Marking tags

Type	Qty.	Order No.
ZQV 2.5N/2	24 A 60	1527540000
ZQV 2.5N/10	24 A 20	1527690000
ZAP/TW ZTTR2.5	50	1865520000
ZEW 35	20	9540000000
SDIS SLIM 0.6X3.5X100	1	2749610000
PS 2.3 RT	20 mA 20	0180400000
SIHA 3/G20	6.3 A 25	7921560000
SIHA 3/G20/LD 10-36V	25	7921570000
SIHA 3/G20/LD 140-250V	25	7921600000
BEST	50	1833100000
BEST/DRBR	22 A 50	1878570000
BEST/D	1 A 50	1878560000
TNST	20 A 50	1833090000
DEK 5/5 MC NE WS	1000	1609801044
DEK 5/5 MM WS	800	2007110000
WS 8/5 MM WS	800	2007150000

For detailed information on other accessories and application in the online catalogue

