


Power distribution

Screw connection



WDK 10 SET LS

10 mm²

Width/Height/Depth	mm
max. current / max. cond. cross-section	A/mm ²
Max. clamping range	mm ²

49.5 x 85 x 69	
70 / 16	
1.5... 16	

Technical data

Rated data	
Rated voltage	V
Rated current	A
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Tightening torque / Clamping screw	Nm
Stripping length / Blade size	mm/-
2 conductors with same cross-section (H05V/H07V)	
Solid / Stranded	-
Flexible / Flexible with ferrule	-
Note	

Ordering data


Version	
	dark beige
	with PE foot
	dark beige / green / yellow
Note	

Accessories

Screwable cross-connection	
	2-pole
	10-pole
End plate / Partition plate	
	dark beige
	Blue
End bracket	
	dark beige
	dark beige, screwable
Screwdriver	
	Standard
Cover	
	Blank, white
	Blank, yellow
Marking tags	
Cross-connector	
	black
	blue
	red

For detailed information on other accessories and application in the online catalogue

WDK 10 SET BCD

10 mm²

29.7 x 85 x 69	
70 / 16	
1.5... 16	

IEC 60947-7-1 (-7-2)


IEC	UL	CSA	EN 60079-7
800	600	600	
57	64	64	
10	AWG 18...6	AWG 18...6	
8 kV / 3			
B6 / V-0			
CE   			
Rated connection		Further connection	
1.5...16 / 1.5...16			
1.5...16 / 1.5...16			
1.2...1.9 / (M 4)			
12 / 1.0 x 5.5 mm			

Type	Qty.	Order No.
WDK 10 SET BCD	1	1415540000
Note		


Type	Qty.	Order No.
WQV 10/2	76 A 50	1052560000
WQV 10/10	63 A 20	1052460000
WAP WDK10	20	1186720000
WAP WDK10 BL	20	1186730000
WEW 35/2	50	1061200000
SDS 1.0X5.5X150	1	2749380000
WAD 8 MC NE WS	48	1112940000
WAD 8 MC NE GE	48	1112950000
DEK 5/5 MC NE WS	1000	1609801044

For detailed information on other accessories and application in the online catalogue

MAK 2.5

2.5 mm²

6.2 x 88 x 63
31 / 4
0.13...4



IEC 60947-7-1 (-7-2)

IEC	UL	CSA	EN 60079-7
500	300	300	
24	10	10	
2.5	AWG 26...12	AWG 26...12	
6 kV / 3			
A3 / V-0			


CE ENE

Rated connection	Further connection
0.5...4 / 0.5...4	
0.5...4 / 0.5...2.5	
0.4...0.6 / (M 2.5)	
8 / 0.6 x 3.5 mm	
0.5...1 / 0.5...1	
0.5...1 / 0.5...0.75	


Type	Qty.	Order No.
MAK 2.5 DB	50	7917030000

Type	Qty.	Order No.
AP MAK2.5 DB	20	7917000000
WEW 35/1	50	1059000000
SDIS 0.6X3.5X100	1	2749810000
DEK 5/5 MC NE WS	1000	1609801044
VQB 1.5/50 SW	17.5 A 5	1635120000
VQB 1.5/50 BL	17.5 A 5	1633280000
VQB 1.5/50 RT	17.5 A 5	1633290000

VLI 1.5

1.5 mm²

6.15 x 79.5 x 63
24 / 4
0.13...4



IEC 60947-7-1

IEC	UL	CSA	EN 60079-7
250	300		
17.5	10		
1.5	AWG 26...12		
4 kV / 3			
A3 / V-0			

CE ENE

Rated connection	Further connection
0.5...4 / 0.5...2.5	
0.5...4 / 0.5...2.5	
0.4...0.6 / (M 2.5)	
8 / 0.6 x 3.5 mm	

Type	Qty.	Order No.
VLI 1.5 DB	50	1784120000
VLI 1.5/PE DB	50	1784130000

Type	Qty.	Order No.
AP VLI1.5 DB	20	1784150000
WEW 35/1	50	1059000000
SDIS 0.6X3.5X100	1	2749810000
DEK 5/5 MC NE WS	1000	1609801044
VQB 1.5/50 SW	17.5 A 5	1635120000
VQB 1.5/50 BL	17.5 A 5	1633280000
VQB 1.5/50 RT	17.5 A 5	1633290000

