


Spring connection with tension clamp technology (Z-Series)

Feed-through terminal blocks

ZDU 4

4 mm²

Two connections



Width/Height/Depth	mm
max. current / max. cond. cross-section	A/mm ²
Max. clamping range	mm ²

6.1 x 62 x 43

41 / 6

0.13...6



Technical data

Rated data	
Rated voltage	V
Rated current	A
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Stripping length / Blade size	mm/-
Note	

Ordering data

Version	
	dark beige
	Blue
Note	

Accessories


Plug-in cross-connection	
	2-pole
	4-pole
	10-pole
End plate / Partition plate	
	dark beige
	Blue
End bracket	
	dark beige
Test adapter	
	Standard
	With spigot
Screwdriver	
	Standard
Reducing sleeves	
	for conductors < 0.5 mm ² / AWG 20
	for conductors < 1.0 mm ² / AWG 18
Cover	
	With lightning flash symbol
Marking tags	

For detailed information on other accessories and application in the online catalogue

ZDU 4/3 AN

4 mm²

Three connections



6.1 x 83.5 x 43

41 / 6

0.13...6



IEC 60947-7-1		Ex eb II	C Gb		II 2 G D
IEC	UL	CSA	EN 60079-7		
800		600	550		
32		35	28		
4		AWG 26...10	6 mm²		
8 kV / 3					
A4 / V-0					
       		DEMKO15ATEX1467U			
Rated connection					
0.5...6 / 0.5...6					
0.5...6 / 0.5...4					
12 / 0.6 x 3.5 mm					

Type	Qty.	Order No.
ZDU 4/3AN	50	7904180000
ZDU 4/3AN BL	50	7904190000

Type		Qty.	Order No.
ZQV 4/2 GE	32 A	60	1608950000
ZQV 4/10 GE	32 A	20	1609030000
ZAP/TW 4/3AN		20	7904100000
ZAP/TW 4/3AN BL		20	7904110000
ZEW 35		20	9540000000
ZTA 2 ZDU4	9 A	25	1609060000
ZTA 2/ZA ZDU4	9 A	25	1609070000
SDIS SLIM 0.6X3.5X100		1	2749610000
ZRH 4/1 WS		1000	1636640000
ZAD 2/4		20	1609080000
DEK 5/6 MC NE WS		1000	1609820000
WS 8/6 MM WS		600	2007160000
DEK 5/6 MM WS		600	2007120000