



Fuse terminal blocks

6 mm²

Width/Height/Depth	mm
max. current / max. cond. cross-section	A/mm ²
Max. clamping range	mm ²

6.3 / 10

0.5...10



IEC 60947-7-3

Rated data	
Rated voltage to adjoining terminal	V
Rated current	A
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Tightening torque / Clamping screw	Nm
Blade size	

IEC	UL	CSA	EN 60079-7
500			
6.3			
6	AWG 22...8	AWG 20...8	
	/ 3		
	V-0		



Rated connection
0.5...10 / 1.5...10
0.5...10 / 0.5...6
0.8...1.6 / (M 3.5)
0.8 x 4.0 mm

Note

Version	10-36 V AC/DC, with LED
	30-70 V AC/DC, with LED
	60-150 V AC/DC, with LED
	140-250 V AC/DC, with LED

Note

Type	Qty.	Order No.
WSI 6/2/LD 10-36V LLC	25	1119800000
WSI 6/2/LD 30-70V LLC	25	1119810000
WSI 6/2/LD 60-150V LLC	25	1119820000
WSI 6/2/LD 250AC LLC	25	1119790000

Screwable cross-connection	2-pole
	10-pole
	Lock washer
	Mounting screw

End plate / Partition plate					
				dark beige	
				dark beige	

End bracket dark beige

Screwdriver	Standard
--------------------	----------

Marking tags

Type	Qty.	Order No.
QL 2 SAK16	76 A 50	0470700000
QL 10 SAK16	76 A 20	0471000000
SS M3 D 128-A 3	50	0164400000
KISC M3X5	100	1052100000

WAP 2.5-10	50	1050000000
WAP 16+35 WTW 2.5-10	20	1050100000

WEW 35/2	50	1061200000
----------	----	------------

SDS 0.8X4.0X100	1	2749360000
-----------------	---	------------

DEK 5/8 MC NE WS	800	1856740000
WS 12/6.5 MC NE WS	540	1609920000

For detailed information on other accessories and application in the online catalogue