




Spring connection with tension clamp technology (Z-Series)
Pluggable terminal blocks

ZP 4/1AN 4 mm²
1...16-pole



Width/Height/Depth	mm
max. current / max. cond. cross-section	A/mm²
Max. clamping range	mm²

6.5 x 22.5 x 47.5
32 / 6
0.13...6

Technical data

Rated data	
Rated voltage	V
Max. voltage of clamp support & pluggable system	-
Rated current	A
for wire cross-section	mm²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm²
Flexible / Flexible with ferrule	mm²
Stripping length / Blade size	mm/-
Note	

In accordance with IEC 60947-7-1			
IEC	UL	CSA	EN 60079-7
800	600	600	
32	28	28	
4	AWG 26...10	AWG 26...10	
	8 kV / 3		
	A3 / V-0		
CE   			
Rated connection		Plug-in connection	
0.5..6			
0.5..6 / 0.5..4			
12 / 0.6 x 3.5 mm			

Ordering data

Version	
1-pole	
2-pole	
3-pole	
4-pole	
5-pole	
6-pole	
7-pole	
8-pole	
9-pole	
10-pole	
11-pole	
12-pole	
13-pole	
14-pole	
15-pole	
16-pole	
17-pole	
1-pole (green)	
Note	

Type	Qty.	Order No.
ZP 4/1AN/1	50	1848340000
ZP 4/1AN/2	25	1854990000
ZP 4/1AN/3	25	1855000000
ZP 4/1AN/4	25	1855010000
ZP 4/1AN/5	20	1855020000
ZP 4/1AN/6	20	1855030000
ZP 4/1AN/7	20	1855040000
ZP 4/1AN/8	20	1855050000
ZP 4/1AN/9	10	1855060000
ZP 4/1AN/10	10	1855070000
ZP 4/1AN/11	20	1855080000
ZP 4/1AN/12	10	1855090000
ZP 4/1AN/13	10	1855100000
ZP 4/1AN/14	10	1855110000
ZP 4/1AN/1 GN	50	1854980000
Note		

Accessories

Plug-in cross-connection	
2-pole	
10-pole	
Test adapter	
Standard	
Screwdriver	
Standard	
Protective strip	
DIN A4 sheets	
Paper	
Marking tags	
For detailed information on other accessories and application in the online catalogue	

Type	Qty.	Order No.
SDIS SLIM 0.6X3.5X100	1	2749610000
DEK 5/5 MC NE WS	1000	1609801044
WS 10/6 MC NE WS	600	1828450000
Note		