


WDK 4N V

4 mm²

Both levels at one potential
Compact design



Width/Height/Depth	mm
max. current / max. cond. cross-section	A/mm ²
Max. clamping range	mm ²

6.1 x 60.7 x 63.25	
35 / 6	
0.13...6	

Ex eb II
C Gb II 2 G D

IEC 60947-7-1	UL	CSA	EN 60079-7
800	600	300	550
32	35	30	30
4	AWG 26...10	AWG 26...10	6 mm ²

8 kV / 3
A4 / V-0

DEMKO15ATEX1346U

Rated connection	Further connection
0.5...6 / 1.5...6	
0.5...4 / 0.5...4	
0.5...1 / (M 3)	
8 / 0.6 x 3.5 mm	

0.5...1.5 / 0.5...1.5

Technical data

Rated data	
Rated voltage	V
Rated current	A
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Tightening torque / Clamping screw	Nm
Stripping length / Blade size	mm/-
2 conductors with same cross-section (H05V/H07V)	
Solid / Stranded	-
Flexible / Flexible with ferrule	mm ²
Note	

Ordering data

Version	
dark beige	
Blue	
dark beige / blue	
Note	


Accessories

Plug-in cross-connection	
2-pole	
10-pole	
End plate / Partition plate	
dark beige	
Blue	
dark beige	
End bracket	
dark beige	
Marking tags	
Screwable cross-connection	
2-pole	
10-pole	
Cover	
Blank, white	
Blank, yellow	
Screwdriver	
Standard	

For detailed information on other accessories and application in the online catalogue

WDK 10

10 mm²



9.9 x 85 x 69	
70 / 16	
1.5...16	

IEC 60947-7-1

IEC	UL	CSA	EN 60079-7
800	600	600	
57	64	64	
10	AWG 18...6	AWG 18...6	

8 kV / 3
B6 / V-0

Rated connection	Further connection
1.5...16 / 1.5...16	
1.5...16 / 1.5...16	
1.2...1.9 / (M 4)	
12 / 1.0 x 5.5 mm	

Type	Qty.	Order No.
WDK 10	50	1186740000
WDK 10 BL	50	1186750000

Type	Qty.	Order No.
WAP WDK10	20	1186720000
WAP WDK10 BL	20	1186730000
WEW 35/2	50	1061200000
DEK 5/5 MC NE WS	1000	1609801044
WDV 10/2	76 A 50	1052560000
WDV 10/10	63 A 20	1052460000
WAD 8 MC NE WS	48	1112940000
WAD 8 MC NE GE	48	1112950000
SDS 1.0X5.5X150	1	2749380000