


Spring connection with tension clamp technology (Z-Series)

Feed-through terminal blocks

ZDU 2.5


2.5 mm²

Two connections



Width/Height/Depth	mm
max. current / max. cond. cross-section	A/mm ²
Max. clamping range	mm ²

5.1 x 59.5 x 38.5
30 / 4
0.05...4



Technical data

Rated data	
Rated voltage	V
Rated current	A
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Stripping length / Blade size	mm/-
Note	

Ordering data

Version	
	dark beige
	Blue
Note	

Accessories


Plug-in cross-connection	
	2-pole
	4-pole
	10-pole
End plate / Partition plate	
	dark beige
	Blue
End bracket	
	dark beige
Test adapter	
	Standard
	With spigot
Screwdriver	
	Standard
Reducing sleeves	
	for conductors < 0.5 mm ² / AWG 20
	for conductors < 1.0 mm ² / AWG 18
Cover	
	With lightning flash symbol
Marking tags	

For detailed information on other accessories and application in the online catalogue


ZDU 2.5/3AN

2.5 mm²

Three connections



5.1 x 64.5 x 38.5
31 / 4
0.05...4



Rated data	
Rated voltage	V
Rated current	A
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Stripping length / Blade size	mm/-
Note	

Version	
	dark beige
	Blue
Note	

Type	Qty.	Order No.
ZDU 2.5/3AN	100	1608540000
ZDU 2.5/3AN BL	100	1608550000
Accessories		
Type	Qty.	Order No.
ZQV 2.5/2	24 A 60	1608860000
ZQV 2.5/10	24 A 20	1608940000
ZAP/TW 2 DB	50	1608770000
ZAP/TW 2 BL	50	1608780000
ZEW 35	20	9540000000
ZTA 1	9 A 25	1609040000
ZTA 1/ZA	9 A 25	1609050000
SDIS SLIM 0.6X3.5X100	1	2749610000
ZRH 2.5/1 WS	1000	1614300000
ZRH 2.5/2 GR/VO	1000	1614290000
ZAD 1/4	20	1609110000
DEK 5/5 MC NE WS	1000	1609801044
WS 10/5 MC NE WS	720	1635000000
DEK 5/5 MM WS	800	2007110000

For detailed information on other accessories and application in the online catalogue