

Screw connection with clamping yoke technology (W-Series)


Feed-through terminal blocks

Identically contoured design of 2.5 to 10 mm² with identical end plates and partitions. An unmatched combination of many advantages!
The compact terminals are impressive for their small size and rated cross-section capacity.

WDU 16

16 mm²

With peg for higher connection stability



11.9 x 60 x 62.5
101 / 25
0.82...25



IEC 60947-7-1
Ex eb II
C Gb II 2 G D

IEC	UL	CSA	EN 60079-7
1000	600	600	690
76	85	85	76
16	AWG 18...4	AWG 18...6	16 mm ²

8 kV / 3
B7 / V-0

DEMKD14ATEX1338U

Rated connection	Further connection
1.5...16 / 1.5...25	
1.5...25 / 1.5...16	
3...4 / (M 5)	
16 / 1.0 x 5.5 mm	

Rated connection	Further connection
1.5...6 / 1.5...6	
1.5...6 / 1.5...6	

Width/Height/Depth	mm
max. current / max. cond. cross-section	A/mm ²
Max. clamping range	mm ²

Technical data

Rated data	
Rated voltage	V
Rated current	A
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Tightening torque / Clamping screw	Nm
Stripping length / Blade size	mm/-
2 conductors with same cross-section (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Note	

Ordering data

Version	
	dark beige
	without peg / dark beige
	with peg / blue
	with peg / dark beige
Note	


Accessories

Screwable cross-connection	
	2-pole
	10-pole
End plate / Partition plate	
	dark beige
	Blue
End bracket	
	dark beige, screwable
	dark beige
Cover	
	black/yellow
	white
	Blank, yellow
	Blank, white
Marking tags	

For detailed information on other accessories and application in the online catalogue

WDUB 16

16 mm²



9.9 x 65 x 47
76 / 16
0.5...16



IEC 60947-7-1

IEC	UL	CSA	EN 60079-7
1000	600		
76	65		
16			

8 kV / 3
B6 / V-0

Rated connection	Further connection
0.5...16 / 0.5...16	
0.5...10 / 0.5...10	
1.2...1.9 / (M 4)	
20 / 0.8 x 4.0 mm	

Rated connection	Further connection

Type	Qty.	Order No.
WDUB 16	20	2868370000
Note		

Type	Qty.	Order No.
WQV 10/2	76 A 50	1052560000
WQV 10/10	63 A 20	1052460000
WEW 35/2	50	1061200000
WAD 8 MC B GE/SW	48	1120470000
WAD 8 MC NE WS	48	1112940000
DEK 5/5 MC NE WS	1000	1609801044
WS 12/5 MC NE WS	720	1609860000


For detailed information on other accessories and application in the online catalogue

WDU 16 IR

16 mm²

WDU 16N

16 mm²



Suitable for power distribution
Compact design

Width/Height/Depth	mm
max. current / max. cond. cross-section	A/mm ²
Max. clamping range	mm ²

11.9 x 60 x 62.5
101 / 25
0.82...25

12 x 60 x 46.5
101 / 25
1.5...25

Technical data

Rated data	
Rated voltage	V
Rated current	A
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Tightening torque / Clamping screw	Nm
Stripping length / Blade size	mm/-
2 conductors with same cross-section (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Note	

IEC 60947-7-1

Ex eb II
C Gb II 2 G D

IEC	UL	CSA	EN 60079-7
1000	600	600	690
76	85	85	76
16	AWG 18...4	AWG 18...6	16 mm ²

8 kV / 3
B7 / V-0

DEMKO14ATEX1338U

Rated connection	Further connection
1.5...16 / 1.5...25	
1.5...25 / 1.5...16	
3...4 / (M 5)	
16 / TX 15	
1.5...6 / 1.5...6	
1.5...6 / 1.5...6	

IEC 60947-7-1

IEC	UL	CSA	EN 60079-7
690	600	300	
76	70	70	
16	AWG 14...6	AWG 14...6	

8 kV / 3
B7 / V-0

Rated connection	Further connection
1.5...16 / 1.5...25	
1.5...16 / 1.5...16	
1.2...2.4 / (M 4)	
12 / 1.0 x 5.5 mm	
1.5...4 / 1.5...4	

Ordering data

Version	
	dark beige
	Blue
Note	

Type	Qty.	Order No.
WDU 16 IR	50	1393390000

Type	Qty.	Order No.
WDU 16N	50	1036100000
WDU 16N BL	50	1036180000

Accessories

Screwable cross-connection	
	2-pole
	10-pole
	4-pole
End plate / Partition plate	
	dark beige
	Blue
End bracket	
	dark beige, screwable
	dark beige
Cover	
	black/yellow
	white
Marking tags	
Testing / Checking	Standard

Type	Qty.	Order No.
WQV 16/2	101 A 50	1053260000
WQV 16/10	101 A 10	1053360000
WAP 16+35 WTW 2.5-10	20	1050100000
WAP 16+35 WTW 2.5-10 BL	20	1050180000
WEW 35/1	50	1059000000
WAD 12 MC B GE/SW	32	2445090000
WAD 12 MC NE WS	32	2445070000
DEK 5/5 MC NE WS	1000	1609801044
WS 12/5 MC NE WS	720	1609860000

Type	Qty.	Order No.
WQV 16N/2	76 A 50	1636560000
WQV 16N/4	76 A 50	1636580000
WTW EN	20	1058800000
WEW 35/2	50	1061200000
WAD 12 MC B GE/SW	32	2445090000
WAD 12 MC NE WS	32	2445070000
DEK 5/5 MC NE WS	1000	1609801044
WS 10/12 MC NE WS	300	1905970000
WTA 2 WDU2.5-10	6 A 25	1632320000


For detailed information on other accessories and application in the online catalogue




WDU 35 IK

35 mm²

Hexagonal socket / spigot for good connection stability



16 x 60 x 62.5
150 / 50
2.5...50



Ex eb II
C Gb II 2 G D

IEC 60947-7-1

IEC	UL	CSA	EN 60079-7
1000	600	600	690
125	150	150	115
35	AWG 12...NaN	AWG 12...NaN	35 mm ²

8 kV / 3

B8 / V-0

DEMKO14ATEX1338U

Rated connection	Further connection
2.5...16 / 2.5...50	
2.5...35 / 2.5...35	
4...6 / (M 6)	
18 / S4 (DIN 6911)	
/ 16...16	
2.5...16 / 2.5...16	

Type	Qty.	Order No.
WDU 35/IK	25	1020600000
WDU 35/IK BL	25	1020680000
WDU 35/IK/ZA	25	1029000000

Type	Qty.	Order No.
WQV 35/2	138 A 50	1053060000
WQV 35/10	112 A 10	1053160000
WAP 16+35 WTW 2.5-10	20	1050100000
WAP 16+35 WTW 2.5-10 BL	20	1050180000
WEW 35/1	50	1059000000
WAD 12 MC B GE/SW	32	2445090000
WAD 12 MC NE WS	32	2445070000
DEK 5/5 MC NE WS	1000	1609801044
WS 12/6.5 MC NE WS	540	1609920000


WDU 35N

35 mm²

Suitable for power distribution
Compact design



16 x 66 x 50.5
150 / 50
2.5...50



Ex eb II
C Gb II 2 G D

IEC 60947-7-1

IEC	UL	CSA	EN 60079-7
500	1000		352
125	150		110
35	AWG 12...0	AWG 12...2	35 mm ²

6 kV / 3

B8 / V-0

DEMKO14ATEX1338U

Rated connection	Further connection
2.5...16 / 2.5...50	
2.5...35 / 2.5...35	
4...5 / (M 6)	
18 / 6.5 x 1.2 mm	
2.5...6 / 2.5...6	

Type	Qty.	Order No.
WDU 35N	20	1040400000
WDU 35N BL	20	1040480000

Type	Qty.	Order No.
WQV 35N/2	125 A 20	1079200000
WQV 35N/4	125 A 20	1079400000
WTW EN	20	1058800000
WEW 35/2	50	1061200000
WAD 16N GE BED	50	1083600000
DEK 5/5 MC NE WS	1000	1609801044
WS 12/6.5 MC NE WS	540	1609920000

