

Instrument transformer wiring

Screw connection



Width/Height/Depth	mm
max. current / max. cond. cross-section	A
Max. clamping range	mm ²

Technical data

Rated data	
Rated voltage	V
Rated current	A
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Tightening torque / Clamping screw	Nm
Tightening torque Separating screw	Nm
Stripping length / Blade size	mm/-

Note


Ordering data

Version	
	With socket
	without socket
Note	

Accessories

Screwable cross-connection	
	2-pole
	3-pole
	4-pole
	10-pole
End plate / Partition plate	
	dark beige
End bracket	
	dark beige
Cross-connection slider	
	2-pole
	Mounting screw for QVS
Testing / Checking	
	Test plug
	Socket
	Standard
Marking tags	


WTL 4

4 mm²

6.1 x 61.3 x 39.9


41 / 6

0.13...6



IEC	UL	CSA	EN 60079-7
500	300	300	
32	28	28	
4	AWG 26...10	AWG 26...10	
6 kV / 3			
A3 / V-0			
CE CB IEC UL			
Rated connection			
0.5...6 / 1.5...4			
0.5...4 / 0.5...4			
0.4...0.7 / (M 2.5)			
0.5...0.7			
10 / 0.6 x 3.5 mm			


WTL 4/2

4 mm²

6 x 56.5 x 48.5

11 / 6

0.13...6



IEC	UL	CSA	EN 60079-7
500	300	150	
10	8	8	
4	AWG 26...10	AWG 26...10	
6 kV / 3			
A4 / V-0			
CE CB IEC UL			
Rated connection			
0.5...6 / 1.5...6			
0.5...6			
0.5...0.8 / (M 3)			
10 / 0.6 x 3.5 mm			

Type	Qty.	Order No.
WTL 4/2 STB	50	1881650000

Type	Qty.	Order No.
WAP WTL4/2	50	1881640000
WEW 35/2	50	1061200000
WTA 8 TN	6 A 25	1915450000
WS 12/6 MC NE WS	600	1609900000

For detailed information on other accessories and application in the online catalogue