


ZMAK 2.5


2.5 mm²

Motor-supply terminal



Width/Height/Depth	mm
max. current / max. cond. cross-section	A/mm ²
Max. clamping range	mm ²

5.1 x 102 x 69.5
31 / 4
0.13...4



Technical data

Rated data	
Rated voltage	V
Rated current	A
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Stripping length / Blade size	mm/-
Note	

IEC 60947-7-1 (-7-2)

IEC	UL	CSA	EN 60079-7
400	300	300	
24	25	25	
2.5	AWG 26...12	AWG 26...12	
6 kV / 3			
A3 / V-0			
CE ENEC ENEC ENEC			
Rated connection			
0.5...4			
0.5...4 / 0.5...2.5			
10 / 0.6 x 3.5 mm			
Note			

Ordering data

Version	dark beige
Note	

Accessories

End plate / Partition plate	dark beige
End bracket	dark beige
Screwdriver	Standard
Reducing sleeves	for conductors < 0.5 mm ² / AWG 20 for conductors < 1.0 mm ² / AWG 18
Test adapter	Standard
Marking tags	

For detailed information on other accessories and application in the online catalogue


ZMAK 2.5 690 V

2.5 mm²

Motor-supply terminal



6.1 x 102 x 69.5
31 / 4
0.13...4



IEC 60947-7-1 (-7-2)

IEC	UL	CSA	EN 60079-7
690	300		
24	25		
2.5	AWG 26...12		
6 kV / 3			
A3 / V-0			
CE ENEC ENEC ENEC			
Rated connection			
0.5...4			
0.5...4 / 0.5...2.5			
10 / 0.6 x 3.5 mm			
Note			

Type	Qty.	Order No.
ZMAK 2.5 690V	25	1027550000
The ZMAK 2.5 690 V with pre-assembled end plate and a width of 6.1 mm.		

Type	Qty.	Order No.
ZAP ZMAK2.5	10	1768010000
ZEW 35	20	9540000000
SDIS SLIM 0.6X3.5X100	1	2749610000
ZRH 1.5H/1	1000	1678810000
ZRH 1.5H/2	1000	1678800000
ZTA 1	9 A 25	1609040000
DEK 5/5 MC NE WS	1000	1609801044
WS 12/5 MC NE WS	720	1609860000
DEK 5/5 MM WS	800	2007110000
WS 8/5 MM WS	800	2007150000