

Spring connection with tension clamp technology (Z-Series) PE terminal blocks

ZPE 2.5-2

2.5 mm²

Two connections



Width/Height/Depth	mm
max. current / max. cond. cross-section	-/mm ²
Max. clamping range	mm ²

5.1 x 50.5 x 43.5	
/ 4	
0.13...4	

Technical data

Rated data	
for wire cross-section	mm ²
Rated voltage to adjoining terminal	V
Rated impulse withstand voltage to adjacent terminal	kV
Rated short-time current	
Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Twin wire-end ferrule	-
Stripping length / Blade size	mm/-
Note	

Ordering data

Version	Green/yellow
Note	

Accessories

End plate / Partition plate	dark beige
End bracket	dark beige
Test adapter	With spigot
Screwdriver	Standard
Reducing sleeves	for conductors < 0.5 mm ² / AWG 20 for conductors < 1.0 mm ² / AWG 18
Marking tags	

For detailed information on other accessories and application in the online catalogue

ZPE 2.5-2/3AN

2.5 mm²

Three connections



5.1 x 50.5 x 43.5	
/ 4	
0.13...4	

IEC 60947-7-2		Ex eb II C Gb	 II 2 G D
IEC	UL	CSA	EN 60079-7
2.5	AWG 26...12	AWG 26...14	4 mm ²
800			
8			
	300 A (2.5 mm ²)		
	3		
	A2 / V-0		
     			
Rated connection			
0.5...2.5			
0.5...2.5 / 0.5...1.5			
10 / 0.6 x 3.5 mm			

Type	Qty.	Order No.
ZPE 2.5-2/3AN	50	1706090000
Note		

Type	Qty.	Order No.
ZAP/TW7	50	1706110000
ZEW 35	20	9540000000
ZTA 4	11 A 25	1688110000
SDIS SLIM 0.6X3.5X100	1	2749610000
ZRH 1.5H/1	1000	1678810000
ZRH 1.5H/2	1000	1678800000
WS 8/5 MM WS	800	2007150000
DEK 5/5 MM WS	800	2007110000
Note		


ZPE 2.5-2/4AN

2.5 mm²

Four connections



5.1 x 50.5 x 43.5
/ 4
0.13...4



IEC 60947-7-2 Ex eb II C Gb II 2 G D

IEC	UL	CSA	EN 60079-7
2.5	AWG 26...12	AWG 26...14	4 mm ²
800			
8			
	300 A (2.5 mm ²)		
	3		
	A2 / V-0		

Rated connection

0.5...4
0.5...2.5 / 0.5...1.5

10 / 0.6 x 3.5 mm

Type	Qty.	Order No.
ZPE 2.5-2/4AN	50	1706100000

Type	Qty.	Order No.
ZAP/TW7	50	1706110000
ZEW 35	20	9540000000
ZTA 4	11 A 25	1688110000
SDIS SLIM 0.6X3.5X100	1	2749610000
ZRH 1.5H/1	1000	1678810000
ZRH 1.5H/2	1000	1678800000
DEK 5/5 MC NE WS	1000	1609801044
WS 10/5 MC NE WS	720	1635000000
DEK 5/5 MM WS	800	2007110000


ZPE 4-2/2AN

4 mm²

Two connections



6.1 x 61.5 x 45.5
/ 6
0.13...6



IEC 60947-7-2 Ex eb II C Gb II 2 G D

IEC	UL	CSA	EN 60079-7
4	AWG 26...10	AWG 26...10	6 mm ²
800			
8			
	480 A (4 mm ²)		
	3		
	A3 / V-0		

Rated connection

0.5...6
0.5...4 / 0.5...4

10 / 0.6 x 3.5 mm

Type	Qty.	Order No.
ZPE 4-2/2AN	50	1770380000

Type	Qty.	Order No.
ZAP ZDU4-2	50	1770400000
ZEW 35	20	9540000000
ZTA 6/ZA	17.5 A 25	1780660000
SDIS SLIM 0.6X3.5X100	1	2749610000
ZRH 4/1 WS	1000	1636640000
DEK 5/6 MC NE WS	1000	1609820000
WS 12/6 MC NE WS	600	1609900000
DEK 5/6 MM WS	600	2007120000


ZPE 4-2/3AN

4 mm²

Three connections



6.1 x 61.5 x 45.5
/ 6
0.13...6



IEC 60947-7-2 Ex eb II C Gb II 2 G D

IEC	UL	CSA	EN 60079-7
4	AWG 26...10	AWG 26...10	6 mm ²
800			
8			
	480 A (4 mm ²)		
	3		
	A3 / V-0		

Rated connection

0.5...6
0.5...4 / 0.5...4

10 / 0.6 x 3.5 mm

Type	Qty.	Order No.
ZPE 4-2/3AN	50	1770390000

Type	Qty.	Order No.
ZAP ZDU4-2	50	1770400000
ZEW 35	20	9540000000
ZTA 6/ZA	17.5 A 25	1780660000
SDIS SLIM 0.6X3.5X100	1	2749610000
ZRH 4/1 WS	1000	1636640000
DEK 5/6 MC NE WS	1000	1609820000
WS 12/6 MC NE WS	600	1609900000
DEK 5/6 MM WS	600	2007120000