





## AAP21 10 LO

10 mm<sup>2</sup>

12 x 82 x 53.5  
57 / 10  
0.5...10



Ex ec II C Gc II

2 G D



In accordance with IEC 60947-7-1

| IEC | UL         | CSA        | EN 60079-7 |
|-----|------------|------------|------------|
| 250 | 600 (C)    | 600 (C)    |            |
| 57  | 51         | 51         | 57         |
| 10  | AWG 20...6 | AWG 20...6 | 10         |

4 kV / 3

V-0



TUEV17ATEX8063U

## Rated connection


0.5...10 / 0.5...10

0.5...10 / 0.5...10


18 mm

1.0 x 5.5 mm

## AAP21 4 LI

4 mm<sup>2</sup>

6.1 x 82 x 53.5  
32 / 4  
0.14...4



Ex ec II C Gc II

2 G D




In accordance with IEC 60947-7-1

| IEC | UL          | CSA         | EN 60079-7        |
|-----|-------------|-------------|-------------------|
| 250 | 300 (C)     | 300 (C)     |                   |
| 32  | 20          | 20          | 32                |
| 4   | AWG 26...10 | AWG 26...10 | 4 mm <sup>2</sup> |

4 kV / 3

V-0



TUEV17ATEX8063U

## Rated connection


0.5...4 / 0.5...4

0.5...4 / 0.5...4


12 mm

0.6 x 3.5 mm

## AAP21 4 LI

4 mm<sup>2</sup>

6.1 x 82 x 53.5  
32 / 4  
0.14...4



Ex ec II C Gc II

2 G D



In accordance with IEC 60947-7-1

| IEC | UL          | CSA         | EN 60079-7        |
|-----|-------------|-------------|-------------------|
| 250 | 300 (C)     | 300 (C)     |                   |
| 32  | 20          | 20          | 32                |
| 4   | AWG 26...10 | AWG 26...10 | 4 mm <sup>2</sup> |

4 kV / 3

V-0



TUEV17ATEX8063U

## Rated connection

0.5...4 / 0.5...4

0.5...4 / 0.5...4

12 mm

0.6 x 3.5 mm

| Type              | Qty. | Order No.  |
|-------------------|------|------------|
|                   |      |            |
|                   |      |            |
| AAP21 10 LO BL/OR | 20   | 2581800000 |

| Type          | Qty. | Order No.  |
|---------------|------|------------|
| AAP21 4 LI RD | 50   | 2428930000 |
| AAP21 4 LI BL | 50   | 2428960000 |
| AAP21 4 LI OR | 50   | 2581700000 |

| Type             | Qty. | Order No.  |
|------------------|------|------------|
|                  |      |            |
|                  |      |            |
| AAP21 4 LI BL/OR | 50   | 2582530000 |

| Type                  | Qty.     | Order No.  |
|-----------------------|----------|------------|
| ZQV 4N/2 RD           | 32 A 60  | 2460450000 |
| ZQV 4N/10 RD          | 32 A 20  | 2460740000 |
| ZQV 4N/2 BL           | 32 A 60  | 1528040000 |
| ZQV 4N/10 BL          | 32 A 20  | 1528230000 |
| AEP AP21              | 20       | 2429020000 |
| AEB 35 SC/1           | 50       | 1991920000 |
| AEB 35 SCL/1 VO       | 20       | 2661280000 |
| ATPG 1.5-10 L         | 0.2 A 50 | 1991890000 |
| PS 2.0 MC             | 20       | 0310000000 |
| SDIL 0,6X3,5X100      | 1        | 2749140000 |
| DEK 5/5 PLUS MC NE WS | 1000     | 1854490000 |
| DEK 5/8 PLUS MC NE WS | 800      | 1046350000 |
| WS 10/8 PLUS MC NE WS | 420      | 1905950000 |

| Type                    | Qty.     | Order No.  |
|-------------------------|----------|------------|
| ZQV 4N/2 RD             | 32 A 60  | 2460450000 |
| ZQV 4N/10 RD            | 32 A 20  | 2460740000 |
| ZQV 4N/2 BL             | 32 A 60  | 1528040000 |
| ZQV 4N/10 BL            | 32 A 20  | 1528230000 |
| AEP AP21                | 20       | 2429020000 |
| AEB 35 SC/1             | 50       | 1991920000 |
| ZEW 35/2                | 20       | 8630740000 |
| ATPG 1.5-10 L           | 0.2 A 50 | 1991890000 |
| PS 2.0 MC               | 20       | 0310000000 |
| SDIL 0,6X3,5X100        | 1        | 2749140000 |
| WS 10/6 M PLUS MC NE WS | 600      | 2003780000 |
| DEK 5/6 MM WS           | 600      | 2007120000 |
| DEK 5/6 PLUS MC NE WS   | 1000     | 1011320000 |
| WS 8/6 MM WS            | 600      | 2007160000 |

| Type                    | Qty.     | Order No.  |
|-------------------------|----------|------------|
| ZQV 4N/2 RD             | 32 A 60  | 2460450000 |
| ZQV 4N/10 RD            | 32 A 20  | 2460740000 |
| ZQV 4N/2 BL             | 32 A 60  | 1528040000 |
| ZQV 4N/10 BL            | 32 A 20  | 1528230000 |
| AEP AP21                | 20       | 2429020000 |
| AEB 35 SC/1             | 50       | 1991920000 |
| ZEW 35/2                | 20       | 8630740000 |
| ATPG 1.5-10 L           | 0.2 A 50 | 1991890000 |
| PS 2.0 MC               | 20       | 0310000000 |
| SDIL 0,6X3,5X100        | 1        | 2749140000 |
| WS 10/6 M PLUS MC NE WS | 600      | 2003780000 |
| DEK 5/6 MM WS           | 600      | 2007120000 |
| DEK 5/6 PLUS MC NE WS   | 1000     | 1011320000 |
| WS 8/6 MM WS            | 600      | 2007160000 |

## Control voltage distribution PUSH IN connection

### AAP – potential distribution terminal blocks



|                                         |                   |
|-----------------------------------------|-------------------|
| Width/Height/Depth                      | mm                |
| max. current / max. cond. cross-section | A/mm <sup>2</sup> |
| Max. clamping range                     | mm <sup>2</sup>   |

#### Technical data

| Rated data                                           |                 |
|------------------------------------------------------|-----------------|
| Rated voltage                                        | V               |
| Rated current                                        | A               |
| for wire cross-section                               | mm <sup>2</sup> |
| Rated impulse withstand voltage / Pollution severity |                 |
| UL 94 flammability rating                            |                 |
| Approvals                                            |                 |
| Clamped conductors (H05V/H07V)                       |                 |
| Solid / Stranded                                     | mm <sup>2</sup> |
| Flexible / Flexible with ferrule                     | mm <sup>2</sup> |
| Stripping length                                     |                 |
| Blade size                                           |                 |

#### Note

#### Ordering data


| Version |                                                  |
|---------|--------------------------------------------------|
|         | beige / red pusher, 250 V AC/DC, without LED     |
|         | beige / red pusher, 10-36 V AC/DC, with LED      |
|         | beige / red pusher, 30-70 V AC/DC, with LED      |
|         | beige / red pusher, 60-150 V AC/DC, with LED     |
|         | beige / red pusher, 100-250 V AC/DC, with LED    |
|         | beige / orange pusher, 250 V AC/DC, without LED  |
|         | beige / orange pusher, 100-250 V AC/DC, with LED |
|         | beige / blue pusher                              |
|         | beige / orange pusher                            |
|         | blue / orange pusher                             |

#### Note


#### Accessories

| Plug-in cross-connection                                                              |                             |
|---------------------------------------------------------------------------------------|-----------------------------|
|                                                                                       | 2-pole/ red                 |
|                                                                                       | 10-pole/ red                |
|                                                                                       | 2-pole/ blue                |
|                                                                                       | 10-pole/ blue               |
| End plate / Partition plate                                                           |                             |
| End bracket                                                                           |                             |
|                                                                                       | dark beige, screwable       |
|                                                                                       | dark beige, direct mounting |
| Test plug                                                                             |                             |
| Screwdriver                                                                           |                             |
|                                                                                       | Standard                    |
| Marking tags                                                                          |                             |
| G-fuse cartridge, 5 x 20 mm (IEC 60127-2)                                             |                             |
|                                                                                       | 0.25 A fast                 |
|                                                                                       | 0.50 A fast                 |
|                                                                                       | 1.00 A fast                 |
|                                                                                       | 2.00 A fast                 |
| For detailed information on other accessories and application in the online catalogue |                             |

### AAP21 4 FS

4 mm<sup>2</sup>

6.1 x 82 x 82  
6.3 / 4  
0.14...4



Ex ec II C Gc II  
2 G D

In accordance with IEC 60947-7-3

| IEC      | UL          | CSA | EN 60079-7        |
|----------|-------------|-----|-------------------|
| 250      | 150 (C)     |     |                   |
| 6.3      | 10          |     | 6.3               |
| 4        | AWG 26...10 |     | 4 mm <sup>2</sup> |
| 4 kV / 3 |             |     |                   |
| V-0      |             |     |                   |


CE CE RoHS TÜV TUEV17ATEX8064U

| Rated connection  |  |
|-------------------|--|
| 0.5...4 / 0.5...4 |  |
| 0.5...4 / 0.5...4 |  |
| 12 mm             |  |
| 0.6 x 3.5 mm      |  |


| Type                   | Qty. | Order No.  |
|------------------------|------|------------|
| AAP21 4 FS             | 50   | 2428950000 |
| AAP21 4 FS 10-36V      | 50   | 2458990000 |
| AAP21 4 FS 30-70V      | 50   | 2460200000 |
| AAP21 4 FS 60-150V     | 50   | 2460190000 |
| AAP21 4 FS 100-250V    | 50   | 2460180000 |
| AAP21 4 FS OR          | 50   | 2581720000 |
| AAP21 4 FS 100-250V OR | 50   | 2581790000 |

| Type                    | Qty.      | Order No.  |
|-------------------------|-----------|------------|
| ZQV 4N/2 RD             | 32 A 60   | 2460450000 |
| ZQV 4N/10 RD            | 32 A 20   | 2460740000 |
| AEP AP21                | 20        | 2429020000 |
| AEB 35 SC/1             | 50        | 1991920000 |
| AEB 35 SCL/1 V0         | 20        | 2661280000 |
| PS 2.0 MC               | 20        | 0310000000 |
| SDIL 0,6X3,5X100        | 1         | 2749140000 |
| WS 10/6 M PLUS MC NE WS | 600       | 2003780000 |
| DEK 5/6 MM WS           | 600       | 2007120000 |
| WS 8/6 MM WS            | 600       | 2007160000 |
| DEK 5/6 PLUS MC NE WS   | 1000      | 1011320000 |
| G 20/0.25A/F            | 0.25 A 10 | 0430500000 |
| G 20/0.50A/F            | 0.5 A 10  | 0430600000 |
| G 20/1.00A/F            | 1 A 10    | 0430700000 |
| G 20/2.00A/F            | 2 A 10    | 0430900000 |

### AAP21 4 DT

4 mm<sup>2</sup>

6.1 x 82 x 55  
20 / 4  
0.14...4



Ex ec II C Gc II  
2 G D

In accordance with IEC 60947-7-1

| IEC      | UL          | CSA         | EN 60079-7        |
|----------|-------------|-------------|-------------------|
| 250      | 150 (C)     | 150 (C)     |                   |
| 20       | 20          | 20          | 19                |
| 4        | AWG 26...10 | AWG 26...10 | 4 mm <sup>2</sup> |
| 4 kV / 3 |             |             |                   |
| V-0      |             |             |                   |

CE CE RoHS TÜV TUEV16ATEX7939U

| Rated connection  |  |
|-------------------|--|
| 0.5...4 / 0.5...4 |  |
| 0.5...4 / 0.5...4 |  |
| 12 mm             |  |
| 0.6 x 3.5 mm      |  |

| Type             | Qty. | Order No.  |
|------------------|------|------------|
| AAP21 4 DT       | 50   | 2428980000 |
| AAP21 4 DT OR    | 50   | 2581710000 |
| AAP21 4 DT BL/OR | 50   | 2582520000 |

| Type                    | Qty.    | Order No.  |
|-------------------------|---------|------------|
| ZQV 4N/2 BL             | 32 A 60 | 1528040000 |
| ZQV 4N/10 BL            | 32 A 20 | 1528230000 |
| AEP AP21                | 20      | 2429020000 |
| AEB 35 SC/1             | 50      | 1991920000 |
| AEB 35 SCL/1 V0         | 20      | 2661280000 |
| SDIL 0,6X3,5X100        | 1       | 2749140000 |
| WS 10/6 M PLUS MC NE WS | 600     | 2003780000 |
| DEK 5/6 MM WS           | 600     | 2007120000 |
| WS 8/6 MM WS            | 600     | 2007160000 |
| DEK 5/6 PLUS MC NE WS   | 1000    | 1011320000 |