



WPE 2.5 WS

2.5 mm²



Width/Height/Depth	mm
max. current / max. cond. cross-section	-/mm ²
Max. clamping range	mm ²

5.1 x 60 x 46.5
/ 4
0.05...4

Technical data

Rated data	
Rated voltage	-
Rated current	-
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm ²
Flexible / Flexible with ferrule	mm ²
Twin wire-end ferrule	-
Stripping length / Blade size	mm/-

Note

Ordering data

Version
white
Note

Accessories

End plate / Partition plate
dark beige
End bracket
dark beige
Screwdriver
Standard
Marking tags

IEC	UL	CSA	EN 60079-7
2.5			
	/ 3		
	A3 / V-0		
Rated connection			
0.5...4 / 1.5...4			
0.5...4 / 0.5...2.5			
10 / 0.6 x 3.5 mm			

Type	Qty.	Order No.
WPE 2.5 WS	50	1010010000

Type	Qty.	Order No.
WAP 2.5-10	50	1050000000
WEW 35/2	50	1061200000
SDS 0.6X3.5X100	1	2749340000
DEK 5/5 MC NE WS	1000	1609801044
WS 12/5 MC NE WS	720	1609860000

For detailed information on other accessories and application in the online catalogue