

WDK 2.5 FF

1 mm²

Spade connection left and right



Width/Height/Depth	mm
max. current / max. cond. cross-section	A/mm ²
Max. clamping range	-

5.1 x 75.5 x 62.5	F2.8 F2.8 F2.8 F2.8
12 / 1	F2.8 F2.8
...1	

IEC 61210, In accordance with IEC 60947-7-1

Technical data

Rated data	
Rated voltage	V
Rated current	A
for wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	-
Flexible / Flexible with ferrule	-
Tightening torque / Clamping screw	-
Stripping length / Blade size	-/-

IEC	UL	CSA	EN 60079-7
400		300	
12		10	
1		AWG 26...12	
6 kV / 3			
/ V-0			

CE CB CB CB CB

Rated connection	Plug-in connection
/	

Note

Ordering data

Version
dark beige
Note

Type	Qty.	Order No.
WDK 2.5 FF	50	1021700000

Accessories

Screwable cross-connection	
	2-pole
	10-pole
End plate / Partition plate	
	dark beige
	Blue
	dark beige
End bracket	
	dark beige
Cover	
	With lightning flash symbol
	Blank, white
Marking tags	

Type	Qty.	Order No.
WQV 2.5/2	32 A 50	1053660000
WQV 2.5/10	32 A 20	1054460000
WAP WDK2.5	20	1059100000
WAP WDK2.5 BL	20	1059180000
WTW EN	20	1058800000
WEW 35/2	50	1061200000
WAD 4 GE BED	50	1072000000
WAD 4 WS	50	1072100000
DEK 5/5 MC NE WS	1000	1609801044
WS 8/5 MC NE WS	720	1640740000
DEK 5/5 MM WS	800	2007110000

For detailed information on other accessories and application in the online catalogue

