

Fuse cartridges and gauge rings for Weidmüller fuse terminal blocks

Fuse cartridges

for terminal type:
PSI 6/10
WSI 4
WSI 6
AFS 4 2C BK
PSI 6/10 SW
ZSI 2.5
ZSI 2.5-2/2X2AN/G20
ZSI 6-2 2X2.5/G20
KDKS 1/35 DB



Ordering data

G-type fuse cartridges 5 x 20 without indicator in accordance with IEC 60127-2 (VDE 0820 T.2 BI) ¹⁾						
Size (mm)		Rated current	Characteristics	Type	Qty.	Order No.
Cartridge fuse Rated breaking capacity	G-Si. 5 x 20 1.5 kA	0.1	quick-acting	G 20/0.10A/F	10	0430300000
		0.2	quick-acting	G 20/0.20A/F	10	0430400000
		0.25	quick-acting	G 20/0.25A/F	10	0430500000
		0.5	quick-acting	G 20/0.50A/F	10	0430600000
		0.63	quick-acting	G 20/0.63A/F	10	0439000000
		1	quick-acting	G 20/1.00A/F	10	0430700000
		1.6	quick-acting	G 20/1.60A/F	10	0430800000
		2	quick-acting	G 20/2.00A/F	10	0430900000
		2.5	quick-acting	G 20/2.50A/F	10	0431000000
		3.15	quick-acting	G 20/3.15A/F	10	0431100000
		4	quick-acting	G 20/4.00A/F	10	0431200000
		5	quick-acting	G 20/5.00A/F	10	0431300000
		6.3	quick-acting	G 20/6.30A/F	10	0431400000
(M) = medium time-lag; (F) = quick-acting						

Fuse cartridges

for terminal type:
WSI 6



Ordering data

G-type fuse cartridges 5 x 25 with code in acc. with DIN 41576 ¹⁾						
Size (mm)		Rated current	Characteristics	Type	Qty.	Order No.
Cartridge fuse Rated breaking capacity	G-Si. 5 x 25 80 A	0.25	medium time-lag	G 25/0.25A/M GE	10	0546900000
		0.5	medium time-lag	G 25/0.50A/M WS	10	0510300000
		0.8	medium time-lag	G 25/0.80A/M GR	10	0646400000
		1	medium time-lag	G 25/1.00A/M RT	10	0265800000
		2	quick-acting	G 25/2.00A/F BL	10	0192700000
		4	quick-acting	G 25/4.00A/F BR	10	0192800000
		6.3	quick-acting	G 25/6.30A/F GN	10	0192900000
		10	medium time-lag	G 25/10.0A/M RT	10	0193100000
(M) = medium time-lag; (F) = quick-acting						

Fuse cartridges

for terminal type:
WSI 4/2
WSI 6/2 GZ/DEF63



Ordering data

Fuse cartridges 1¼" x ¼" without indicator in acc. with BS 88						
Size (mm)		Rated current	Characteristics	Type	Qty.	Order No.
Cartridge fuse Rated breaking capacity	G-Si. 6.3 x 32 50 kA	0.5	quick-acting	GZ 0.5A/F	10	1460580000
		1	quick-acting	GZ 1.0A/F	10	1460590000
		2	quick-acting	GZ 2.0A/F	10	1460600000
		3	quick-acting	GZ 3.0A/F	10	1460610000
		5	quick-acting	GZ 5.0A/F	10	1460620000
		7	quick-acting	GZ 7.0A/F	10	1460630000
		10	quick-acting	GZ 10.0A/F	10	1460640000
		12.5	quick-acting	GZ 12.5A/F	10	1460650000
(M) = medium time-lag; (F) = quick-acting						

Note: 1) The company SIBA supplies G-type cartridge fuses, 5 x 25 with indicator, also in marine engineering version for 450 V~.