


WTR 2.5/SI

2.5 mm<sup>2</sup>



Width/Height/Depth	mm
max. current / max. cond. cross-section	A/mm <sup>2</sup>
Max. clamping range	mm <sup>2</sup>

5.1 x 60 x 97  
6.3 / 4  
0.05...4

### Technical data

Rated data	
Rated voltage to adjoining terminal	V
Rated current	A
for wire cross-section	mm <sup>2</sup>
Rated impulse withstand voltage / Pollution severity	
UL 94 flammability rating	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / Stranded	mm <sup>2</sup>
Flexible / Flexible with ferrule	mm <sup>2</sup>
Tightening torque / Clamping screw	Nm
Blade size	

IEC 60947-7-3

IEC	UL	CSA	EN 60079-7
400		300 (D)	
6.3		10	
2.5	AWG 22...12	AWG 26...12	
6 kV / 3			
V-0			

CE

Rated connection	
0.5...4 / 1.5...4	
0.5...4 / 0.5...2.5	
0.4...0.8 / (M 2.5)	
0.6 x 3.5 mm	

Note

### Ordering data

Version	
	400 V AC/DC, without LED
	10-36 V AC/DC, with LED
Note	

Type	Qty.	Order No.
WTR 2.5/SI	25	1763940000
WTR 2.5/SI LD 36V	25	1763950000

### Accessories

Plug-in cross-connection	
	2-pole
	10-pole
End plate / Partition plate	
	dark beige
	dark beige
G-fuse cartridge, 5 x 20 mm (IEC 60127-2)	
	0.25 A fast
	0.50 A fast
	1.00 A fast
	2.00 A fast
Screwdriver	
	Standard
Marking tags	

Type	Qty.	Order No.
ZQV 2.5N/2	24 A 60	1527540000
ZQV 2.5N/10	24 A 20	1527690000
WAP 2.5-10		
	50	1050000000
WAP 16*35 WTW 2.5-10		
	20	1050100000
G 20/0.25A/F		
	0.25 A 10	0430500000
G 20/0.50A/F		
	0.5 A 10	0430600000
G 20/1.00A/F		
	1 A 10	0430700000
G 20/2.00A/F		
	2 A 10	0430900000
SDS 0.6X3.5X100		
	1	2749340000
DEK 5/5 MC NE WS		
	1000	1609801044
WS 12/5 MC NE WS		
	720	1609860000
DEK 5/5 MM WS		
	800	2007110000
WS 8/5 MM WS		
	800	2007150000

For detailed information on other accessories and application in the online catalogue

