



GROUND LIGHTS SPECIFICATION SHEET




**COLLINGWOOD
LIGHTING**

01604 495 151
collingwoodlighting.com

 /collingwoodlighting

 /collingwoodlighting

 collingwoodled

GL019 LG

1W, 65lm mini low glare ground light

FEATURES

IK rating	IK07
IP rating	IP68
Colour flexibility	Fixed colour
UGR	<10
Walk Over / Drive Over	Walk over (5mm toughened glass)
Input	350mA / 700mA
LED Lifetime	70,000h L70 B10
CRI	>80Ra
SDCM	3SDCM

INSTALLATION INFORMATION

Cut Out Size	Ø 33mm
Bathroom zone	0
Efficiency	DRIVER DEPENDANT
Construction Material	Stainless steel (316)
Weight	204g
Maximum ambient temperature	50°C
Electric Class (1, 2, 3)	3

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Compact yet powerful fitting

Shallow depth for easy installation

Robust cable for outdoor use

Built-in glare reducing honeycomb baffle

Can also be powered by a 700mA low voltage driver if more light is needed.

Marine-grade stainless steel 316

PHOTOMETRICS @ 25°C

Product code	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
GL019LGFNW	1W	4000K	30°	65	65	262
GL019LGSNW	1W	4000K	12°	65	65	908
GL019LGFWW	1W	3000K	30°	55	55	222
GL019LGSWW	1W	3000K	12°	55	55	768
GL019LGF27	1W	2700K	30°	53	53	214
GL019LGS27	1W	2700K	12°	53	53	740

WIRING INFORMATION


Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PLR/350 1-5	N/A	Yes	No	0	1	5
PLD UNI-DRIVE 350MA	N/A	Yes	Yes (1-10V)	2	1	10

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors
TUBE332	Installation tube
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types



Beam angles: 12° 30°

