

POND LIGHTS SPECIFICATION SHEET



UL030

High output universal LED light

FEATURES

IP rating	IP68
Colour flexibility	Fixed colour
Tilttable	360°
Rotation angle	360°
Dimmable	Yes with suitable driver
Input	700mA
LED Lifetime	70,000h L70 B10
CRI	>80Ra
SDCM	3SDCM

INSTALLATION INFORMATION

Bathroom zone	0
Construction Material	Stainless steel (316) or Brass
Weight	645g
Maximum ambient temperature	50°C
Electric Class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Finish	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
UL030DNBX40	Stainless Steel	4.6W	4000K	12°	490	70	7975
UL030DNBX30	Stainless Steel	4.6W	3000K	12°	480	69	7812
UL030DNBX27	Stainless Steel	4.6W	2700K	12°	470	67	7649
UL030DWBX27	Stainless Steel	4.6W	2700K	40°	470	67	1007
UL030DWBX30	Stainless Steel	4.6W	3000K	40°	480	69	1029
UL030DWBX40	Stainless Steel	4.6W	4000K	40°	490	70	1050
UL030ANAX30	Brass	4.6W	3000K	12°	480	69	7812
UL030ANAX27	Brass	4.6W	2700K	12°	470	67	7649
UL030AWAX30	Brass	4.6W	3000K	40°	480	69	1029
UL030AWAX27	Brass	4.6W	2700K	40°	470	67	1007

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/700 3-9	220-240V	Yes	No	1	1	1
PLD UNI-DRIVE 700mA	N/A	Yes	Yes (1-10V)	2	1	6

ACCESSORIES

JB2 / JB4	Waterproof junction box / Gel filled waterproof connector	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

/collingwoodlighting

/collingwoodlighting

collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Single LED and lens combination for maximum efficiency and optimal light distribution

Complete with wall fixings

Tilt & rotate for adjusting light

Marine grade stainless steel 316

Long lifetime of 70,000hrs

7 year warranty

Light source
energy efficiency:



Beam angles: 12° 40°

