

DECORATIVE WALL LIGHTS + UNDERSHELF LIGHTING

SPECIFICATION SHEET



ML01

Decorative LED mini light

FEATURES

IP rating	IP68
Colour flexibility	Fixed colour
Dimmable	Yes With suitable driver
Input	350mA
LED Lifetime	70,000h L70 B10
CRI	>80Ra or -
SDCM	3SDCM

INSTALLATION INFORMATION

Cut Out Size	Ø 26mm
Bathroom zone	0
Construction Material	Stainless steel (316)
Weight	50g
Maximum ambient temperature	35°C
Electric Class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Wattage	Colour	lm	lm/W	lx @ 1m
ML01 NW	1W	4000K	4	4	0
ML01 WW	1W	3000K	3.6	3	0
ML01 27	1W	2700K	3.5	3.5	0
ML01 AMBER	1W	Amber	-	-	-
ML01 BLUE	1W	Blue	-	-	-
ML01 GREEN	1W	Green	-	-	-
ML01 RED	1W	Red	-	-	-

WIRING INFORMATION

Cable / Flying Lead	1m (0.205mm ² red & black PTFE)
Type of Wiring Required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PLR/350 1-5	220-240V	Yes	No	Hors volume	1	5
PLD UNI-DRIVE 350MA	220-240V	Yes	Yes (1-10V)	2	1	10

ACCESSORIES

CR135	PTFE cable
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
UY2 CONNECTOR	Quick waterproof connector



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

/collingwoodlighting

/collingwoodlighting

collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Small & discreet decorative recessed LED light

Perfect for discreet decorative light in interior and exterior applications

Beam angle:

