

Decorative Wiring Accessories • Smart Lighting Control • Wireless Audio

LEDITB100

LED Dimmer Modules | LED DIMMER MODULES | LED Trailing/Leading Edge Push On/Off Rotary 2 Way
Switching Dimmers

Item Image	Wiring	Dimensions
NO IMAGE		
Primary Range	LED Dimmer Modules	
Insert Type	1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Dimmer Module	
Insert Colour	White	
EAN13 Barcode	5017504088804	
Commodity Code	85365015	
Luckins TSI	403422861	
Dimensions(Nominal)	Module: Height = Width = Depth =	
Weight	43 GR	
Switched Poles	Single	
Current Rating	0.4 Amp	
Voltage	230V-240V	
Maximum Load	5-100W	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Terminal Capacity 1	2X1mm²	
Terminal Capacity 2	2X1.5mm ²	
Earth Terminal Capacity 1	5x1mm ²	
Earth Terminal Capacity 2	4X1.5mm ²	
Earth Terminal Capacity 3	3X2.5mm ²	
Earth Terminal Capacity 4	1X4mm² Multi-Strand	
Earth Terminal Capacity 5	1X6mm ²	
Product Class 1	Face plate muct be earthed	
Ambient Operating Temperature	-5°C to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-2-1	
Additional Notes	Trailing Edge & Leading Edge Dimm	er



making connections beautifully

Decorative Wiring Accessories • Smart Lighting Control • Wireless Audio

LEDITB100

LED Dimmer Modules | LED DIMMER MODULES | LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmers

It is the policy of the company to All products listed conform to current All accessories are manufactured improve products as part of our British or European standard and the under an accredited BS EN ISO 9001: development programme. Therefore, product information is correct at the 2015 Quality Management System. we reserve the right to alter designs time of going to press. and dimensions without prior notice. Illustrations and diagrams are Due to manufacturing processes we reproduced within the limitations of Correct as at 21 April 2022 02:03 PM cannot quarantee an exact colour reproduction and printing process and match and shadings of of certain E&OE are not binding. finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

LEDITB100-LED Dimmer Modules | LED DIMMER MODULES | LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmers