

making connections beautifully

Decorative Wiring Accessories • Smart Lighting Control • Wireless Audio

## 7G244XLEDITB100

Hartland G2 | HARTLAND G2 RANGE | LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmers

Dimmers			
	Wiring	Dimensions	
ltem Image		Hemilton HARTLAND G2 4XLEDITB LEDITB100 2 Way Dimmer	
OCCC	NO IMAGE	144.4	
Primary Range	Hartland G2		
Insert Type	4 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer		
Insert Colour	Satin Steel		
EAN13 Barcode	5051164001940		
Commodity Code	85365015		
Luckins TSI	407521263		
Dimensions(Nominal)	Double: Height = 87.4mm Width = 144.4mm Depth = 4.65mm		
Switched Poles	Single		
Current Rating	0.3A Per Gang		
Voltage	230V AC		
Maximum Load	5-70W Per Gang		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Terminal Capacity 1	2X1mm <sup>2</sup>		
Terminal Capacity 2	2X1.5mm <sup>2</sup>		
Earth Terminal Capacity 1	5x1mm <sup>2</sup>		
Earth Terminal Capacity 2	4X1.5mm <sup>2</sup>		
Earth Terminal Capacity 3	3X2.5mm <sup>2</sup>		
Earth Terminal Capacity 4	1X4mm² Multi-Strand		
Earth Terminal Capacity 5	1X6mm²		
Product Class 1	Face plate muct be earthed		
Ambient Operating Temperature	-5°C to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-2-1		
Additional Notes	Trailing Edge & Leading Edge Dimme	er	



Decorative Wiring Accessories • Smart Lighting Control • Wireless Audio

## 7G244XLEDITB100

Hartland G2   HARTLAND G2 RAN	IGE   LED Trailing/Leading Edge Po Dimmers	ush On/Off Rotary 2 Way Switching
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
reproduced within the limitations of reproduction and printing process and	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 21 April 2022 05:48 PM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84  7C244XLEDITBIOO-Hartland C2 Satin Steel 4g 100W LED 2 Way Push On/Off Rotary Dimmer Satin Steel		Listed in Minimble product selector   Ins. SPlus   Sol   Sol