

making connections beautifully

Decorative Wiring Accessories • Smart Lighting Control • Wireless Audio

IDPWDRYBL-B

GRID-IT | GRID-IT RANGE | Rocker Switch Modules 20AX Double Pole Rocker Module + Printed Legend

······································			
Item Image	Wiring	Dimensions	
NO IMAGE	Live Neutral N IN L IN N CE BS EN 60669 20AX 250V- Double Pole L OUT N Live Neutral To To Load Load	Hemilton GRD-I JOAX Double Pole Rocker Module	
Primary Range	GRID-IT		
Insert Type	20AX Double Pole Rocker Module + Prin	20AX Double Pole Rocker Module + Printed Legend	
Insert Colour	Black Washer Dryer/Black		
EAN13 Barcode	5017504070748		
Commodity Code	85363030		
Luckins TSI	405688412		
Dimensions(Nominal)	Module: Height = Width = Depth =		
Weight	43 GR		
Switched Poles	Double		
Current Rating	20AX		
Voltage	220/250V AC		
Maximum Load	20 Amp inductive		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Contact Gap Minimum	3mm		
Terminal Capacity 1	5x1mm ²		
Terminal Capacity 2	4x1.5mm ²		
Terminal Capacity 3	2x2.5mm ²		
Terminal Capacity 4	1x4mm² Multi-strand		
Terminal Capacity 5	1x6mm²		
Earth Terminal Capacity 1	6x1mm ²		
Earth Terminal Capacity 2	5x1.5mm²		
Earth Terminal Capacity 3	3x2.5mm ²		
Earth Terminal Capacity 4	2x4mm ² Multi-strand		
Earth Terminal Capacity 5	1x6mm ²		
Product Class 1	Face plate must be earthed		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	n Installation Altitude 2000m		

IDPWDRYBL-B-GRID-IT | GRID-IT RANGE | Rocker Switch Modules 20AX Double Pole Rocker Module + Printed Legend

WEB

Hamilton

making connections beautifully

Decorative Wiring Accessories • Smart Lighting Control • Wireless Audio

IDPWDRYBL-B

GRID-IT | GRID-IT RANGE | Rocker Switch Modules 20AX Double Pole Rocker Module + Printed Legend

product information is correct at the time of going to press.2015 Quality Management System.we reserve the right to alter designs and dimensions without prior notice.Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.Correct as at 21 April 2022 05:23 PM E&OER Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YBImage and dimensions without prior notice.	Standard/Approval	BS EN 60669-1	
reproduced within the limitations of reproduction and printing process and are not binding. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB	British or European standard and the product information is correct at the	under an accredited BS EN ISO 9001 :	improve products as part of our development programme. Therefore,
Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB	reproduced within the limitations of reproduction and printing process and	cannot guarantee an exact colour match and shadings of of certain	
Registered in London No. 941624 VAT Registration No. 222 6607 84	Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 E: info@hamilton-litestat.com www.hamilton-litestat.com		COMPREMENTATION Listed in Strimble, Comparison of the graduat selector selector and the sel

WEB