8MWR22WH-W-Sheer | SHEER RANGE | Rocker Switches



## ,

## Decorative Wiring Accessories • Smart Lighting Control • Wireless Audio

## 8MWR22WH-W Sheer | SHEER RANGE | Rocker Switches Wiring **Dimensions** Item Image Hamilton R22 2 Way Rocker NO IMAGE Primary Range Sheer Insert Type 2 gang 10AX 2 Way Rocker White/White Insert Colour EAN13 Barcode 5017504033149 Commodity Code 85363010 Luckins TSI 404397131 Dimensions(Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm 131 GR Weight Switched Poles Single Current Rating 10AX 220/250V AC Voltage Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 $5x1mm^2$ 4x1.5mm<sup>2</sup> Terminal Capacity 2 1x2.5mm<sup>2</sup> Terminal Capacity 3 Terminal Capacity 4 1x4mm<sup>2</sup> Multi-strand Terminal Capacity 5 1x6mm<sup>2</sup> 5x1mm<sup>2</sup> Earth Terminal Capacity 1 Earth Terminal Capacity 2 4x1.5mm<sup>2</sup> 3x2.5mm<sup>2</sup> Earth Terminal Capacity 3 Earth Terminal Capacity 4 1x4mm<sup>2</sup> Multi-strand Earth Terminal Capacity 5 1x6mm<sup>2</sup> Product Class 1 Must be earthed -5° to +40°C Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m

8MWR22WH-W-Sheer | SHEER RANGE | Rocker Switches



Decorative Wiring Accessories • Smart Lighting Control • Wireless Audio

## 8MWR22WH-W

Sheer   SHEER RANGE   Rocker Switches		
Standard/Approval	BS EN 60669-1	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 21 April 2022 05:17 PM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84		Listed in *Trimble groduct selector IDS-Plus (SELTIN-MA1228)