

## WIRED SENSORS | DUAL TEC®

### DUAL TEC® Dual technology detector

ORDER NO. | DT8016MF5



- Sleek, Sturdy Housing
- 16m x 22m detection range
- Power: 9 - 15V DC, 9mA @ 12V DC
- X-Band technology, advanced DualCore™, Signal Processing,
- Passive infrared part with Mirror optics
- Operating temperature: -10°C to 55°C
- Cover and pry-off tamper switch
- Adjustable microwave,
- plug-in electronics and built in EOL resistors

### DUAL TEC® Dual technology detector

ORDER NO. | DT8016F5



- Sleek, Sturdy Housing
- 16m x 22m detection range
- Power: 9 - 15V DC, 9mA @ 12V DC
- X-Band technology, advanced DualCore™, Signal Processing
- Operating temperature: -10°C to 55°C
- Cover and pry-off tamper switch
- Adjustable microwave,
- plug-in electronics and built in EOL resistors

### DUAL TEC® Dual technology detector with Pet Immunity

ORDER NO. | DT8012F5




- Sleek, Sturdy Housing
- 12m x 17m detection range
- Pet Friendly selectivity (45 kg)
- Power: 9 - 15V DC, 9mA @ 12V DC
- X-Band technology, advanced DualCore™, Signal Processing
- Operating temperature: -10°C to 55°C
- Cover and pry-off tamper switch
- Adjustable microwave,
- Plug-in electronics

# FULL RANGE OF WIRED MOTION SENSORS

**DT7360-UK**



**DT906AM-UK**



**DT906AM-UK**



**DT8016AF5**



**DT8016MF5**



**IS3016A**



**DT8016F5**



**IS3016**



**DT8012F5**



**IS3012**



**IS312**



**IS312B**



**DUAL TEC**

**PIR**

More details on the symbols



COMMERCIAL

RESIDENTIAL