

Installation: ceiling mount, install into existing ceiling



1256020



1256024



1256014



1256022

Round


	Lamp	Watt	Input	K	CRI	Lm	IP	Class	Recess depth	Fire	adj*	▲		
MW 1256024	Integral LED	6.1W	CC 350mA▼	2700	80	605	21	◆	Ø86	150	✓	-	✓	✓
MW 1256020	Integral LED	6.1W	CC 350mA▼	3000	80	628	21	◆	Ø86	150	✓	-	✓	✓
MW 1256013	Integral LED	6.1W	CC 350mA▼	2700	80	605	20	◆	Ø92	150	✓	✓	✓	✓

Square


MW 1256021	Integral LED	6.1W	CC 350mA▼	3000	80	628	21	◆	Ø86	150	✓	-	✓	✓
MW 1256026	Integral LED	6.1W	CC 350mA▼	2700	80	605	21	◆	Ø86	150	✓	-	✓	✓
MW 1256014	Integral LED	6.1W	CC 350mA▼	2700	80	605	20	◆	Ø92	150	✓	✓	✓	✓

Twin


MW 1256022	Integral LED	2 x 6.1W	CC 350mA▼	2700	80	1123	20	◆	165x85	150	✓	-	✓	✓
MW 1256019	Integral LED	2 x 6.1W	CC 350mA▼	3000	80	1206	21	◆	165x85	150	✓	-	✓	✓




Aprilia Round




Aprilia Round
Fire Rated



Aprilia Square



Aprilia Square
Fire Rated



Aprilia Twin

◆ Our fire rated downlights comply with all the latest building regulations: Part B - Fire Safety. The downlights have been tested to provide a minimum of 90 minutes fire protection (BS 476: part 21).

▼ Lamp excluded, see P.174