

FLEXIBLE GALVANISED STEEL PVC - CONDUIT



GALVANISED STEEL PVC - CONDUIT

GLANDS

REF	TRADE SIZE	COIL LENGTH	PLAIN HOLE	MALE FIXED	MALE SWIVEL	ID / OD CONDUIT
FPCC 12	12 mm	50 meter	BCG 12 mm	FCG 12 mm	SCG 12 mm	10 / 14 mm
FPCC 16	16 mm	10 - 30 - 50 m	BCG 16 mm	FCG 16 mm	SCG 16 mm	13 / 17 mm
FPCC 20	20 mm	10 - 30 - 50 m	BCG 20 mm	FCG 20 mm	SCG 20 mm	17 / 21 mm
FPCC 25	25 mm	10 - 30 - 50 m	BCG 25 mm	FCG 25 mm	SCG 25 mm	22 / 27 mm
FPCC 32	32 mm	10 - 30 meter	BCG 32 mm	FCG 32 mm	SCG 32 mm	28 / 34 mm
FPCC 40	40 mm	10 - 30 meter	BCG 40 mm	FCG 40 mm	SCG 40 mm	38 / 43 mm
FPCC 50	50 mm	10 - 30 meter	BCG 50 mm	FCG 50 mm	SCG 50 mm	48 / 55 mm

Technical data:

Square locked galvanised steel conduit with PVC cover, good mechanical stability and flexibility.
 Material : galvanised steel. Cover: PVC, self extinguishing Temp. Range : -20°C till +80 °C
 Isolation: IP 40 Standards: EN 50086 galvanised to DIN 53210, Crush resistance to 1500 N
 Colour: Black, grey, cream
 Usage: applications in machine tool and connections for general wiring where light mechanical stress can be obtained. Note: also available in low fire hazard version

CONTRACTOR PACK



GALVANISED STEEL PVC - CONDUIT

GLANDS

REF	TRADE SIZE	COIL LENGTH	MALE FIXED	ID / OD CONDUIT
FPCC 12 CP	12 mm	10 meter	FCG 12 mm	10 / 14 mm
FPCC 16 CP	16 mm	10 meter	FCG 16 mm	13 / 17 mm
FPCC 20 CP	20 mm	10 meter	FCG 20 mm	17 / 21 mm
FPCC 25 CP	25 mm	10 meter	FCG 25 mm	22 / 27 mm
FPCC 32 CP	32 mm	10 meter	FCG 32 mm	28 / 34 mm

Technical data:

Each contractor pack consist of 10 meter conduit and 10 fittings.

ACCESSORIES FITTINGS / CONDUITS



ACCESSORIES FITTINGS / CONDUIT

P - CLIPS			BRASS, NICKEL PLATED, LOCKNUTS		
REF	TRADE SIZE	BOX QTY	REF	TRADE SIZE	BOX QTY
PC 10	10 mm	100			
PC 12	12 mm	100			
PC 16	16 mm	100	BLN 16	16 mm	100
PC 20	20 mm	100	BLN 20	20 mm	100
PC 25	25 mm	100	BLN 25	25 mm	100
PC 32	32 mm	100	BLN 32	32 mm	50
PC 40	40 mm	100	BLN 40	40 mm	50
PC 50	50 mm	100	BLN 50	50 mm	25