


Ducting - Adaptors


Double Airbrick



Cat No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
60905W	220 x 90mm White	145	245	80	0.2	1.6	4.3	8.7	13.9	21.1	27.5	37.4	
60905B	220 x 90mm Brown	145	245	80	0.2	1.6	4.3	8.7	13.9	21.1	27.5	37.4	
60905CS	220 x 90mm Cotswold St.	145	245	80	0.2	1.6	4.3	8.7	13.9	21.1	27.5	37.4	
60905T	220 x 90mm Terracotta	145	245	80	0.2	1.6	4.3	8.7	13.9	21.1	27.5	37.4	

Double Airbrick Adaptor to Rectangular Duct


Fits High Performance Ducting 220 x 90mm to double Airbrick 60905



Cat No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
60977	Double Airbrick Adaptor	-	-	-	-	-	-	-	-	-	-	-	

Double Airbrick Adaptor to Round Duct


Fits 100/125/150mm Round Pipe



Cat No.	Product Type	External Dimensions			Resistance (Pa) at flow rate						
		H	W	D	60 l/s		120 l/s		180 l/s		
60954	Double Airbrick Adaptor	-	-	-	-	-	-	-	-	-	-

High Performance Ducting Adaptor


Fits 125 Channel Ducting 220x90mm to High Performance Ducting



Cat No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
60957	Adaptor	-	-	-	-	-	-	-	-	-	-	-	


Airbrick Adaptor

To connect Flat Channel Ducting and Airbrick Ventilators




Cat No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
1580	Adaptor	-	-	-	-	-	-	-	-	-	-	-	
1590	Adaptor	-	-	-	-	-	-	-	-	-	-	-	

Extended Horizontal Airbrick - For 225mm to 300mm System



Cat No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
1572	Fits Direct to Flat Channel	-	-	-	-	-	-	-	-	-	-	-	
1573	Fits Direct to Flat Channel	-	-	-	-	-	-	-	-	-	-	-	

Slimline Airbrick




Cat. No.	Product Type	Size	Resistance (Pa) at flow rate								
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
45010*	Horizontal Louvre	110x54mm	-	-	-	-	-	-	-	-	
45011	Vertical Louvre	110x54mm	-	-	-	-	-	-	-	-	

* Fits into airbrick adaptor - 40770

Slimline Airbrick

Wall Outlet



Cat. No.	Product Type	Size	Resistance (Pa) at flow rate								
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
55010	Horizontal Louvre	204x60mm	-	-	-	-	-	-	-	-	
55011	Vertical Louvre	204x60mm	-	-	-	-	-	-	-	-	
55012	Low resistance airbrick	204x60mm	-	-	-	-	-	-	-	-	

Slimline Airbrick with Internal Damper



Cat. No.	Product Type	Size	Resistance (Pa) at flow rate								
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
58501	Horizontal Louvre	150x70mm	-	-	-	-	-	-	-	-	
55501	Horizontal Louvre	204x60mm	-	-	-	-	-	-	-	-	

Airbrick Adaptor

For use with Flat Channel Ducting and Slimline Air Bricks



Cat. No.	Product Type	Size	Resistance (Pa) at flow rate								
			8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
40770	Airbrick Adaptor	110x54mm	-	-	-	-	-	-	-	-	

* Fits airbrick 45010