Maniheat Heating Range

NEW

NEW

Panel Heater with 24/7 timer options

The Manrose 24/7 Panel Heaters connect directly to the permanent electricity supply offering two heat output settings depending on your heating needs. The timer option allows user to select one of 12 pre-set programmes or create a customised 'DIY' heating programme. Wall fixtures are included.

- Silent in operation
- Slim and compact in size, only 57mm deep
- High efficiency of airflow with over 95% of used energy creating heat
- User friendly LCD display screen
- 12 pre-set programmes available
- 1 user defined programme available
- Program and real-time clock memory function
- Thermostat for temperature setting (5°C-30°C)
- Adjustable temperature in Normal and Economic modes
- 24 hour On/Off Timer
- Anti-frosting function
- Ionizer function
- Child safety lock
- Over-heat safety protection
- IP24 Rated

Model	HP24TIMPH150T	HP24TIMPH200T
Power	1500W	2000W
Colour	White	White
Heating setting	0.75kW & 1.5kW	1kW & 2kW
Heating area	18-20m²	22-26m²
Voltage	220V-240VAC 50/60Hz	220V-240VAC 50/60Hz
Approval	CE, EMC, LVD, RoHS, REACH	CE, EMC, LVD, RoHS, REACH
Product size HxWxD	400x730x57mm	400x1267x57mm
Packaged size HxWxD	422x975x110mm	442x1312x110mm
Heater weight	6.8kg	8.7kg

Panel Heater with 24 hour countdown timer

The Manrose Panel Heaters with 24 hour countdown timer connect directly to the permanent electricity supply offering three heat output settings depending on your heating needs. The countdown timer can be used to schedule the heater to either turn on or off. Wall fixtures are included.

- Silent in operation
- Slim and compact in size, only 69mm deep
- The sheathed aluminium heating elements contributes to energy efficiency
- Timer (24 hours) to stop/stop working
- Over-heat safety protection
- Electronic thermostat for temperature control
- 24 hour On/Off Timer
- Anti-frost function
- Ionizer function
- Three heat options; Economy, Normal and Express
- Child safety lock
- IP24 Rated

Model	HPTIMPH150T	HPTIMPH200T
Power	1500W	2000W
Colour	White	White
Heat setting	0.5kW, 1kW & 1.5kW	0.8kW, 1.2kW & 2kW
Heating area	18-20m²	22-26m²
Voltage	220V-240VAC 50/60Hz	220V-240VAC 50/60Hz
Approval	CE, EMC, LVD, RoHS, REACH	CE, EMC, LVD, RoHS, REACH
Product size HxWxD	400x595x69mm	400x830x69mm
Packaged size HxWxD	445 x 685 x 125mm	445 x 920 x 125mm
Heater weight	5.8kg	7.7kg
Packaged weight	6kg	8.9kg