

CENTRO CIRCO

LED

CFL



Satin Aluminium
CE(3 or 4)/F



Chrome
CE(3 or 4)/H




Graphite
CE(3 or 4)/G



Brass
CE(3 or 4)/Z



A



B

Size	CE3	CE4
A	108mm	128mm
B	330mm	450mm

LED / Lamp Types

- B22 GLS (lamp not included).
- 21W 2D 4-Pin, 3500K, GR10 Cap.
- 28W / 38W 2D 4-Pin, 3500K, GR10 Cap.
- LED versions.

Materials

- Fascia: Vandal resistant polycarbonate in Brass / Chrome / Satin Aluminium / White / Graphite finish. Other colours available on request. Metallic finishes indoor use only.
- Diffuser: Vandal resistant polycarbonate in Opal (fresnel option available) with self-extinguishing fire properties.
- Body: Vandal resistant polycarbonate in finish to match fascia.
- Back light: Clear vandal resistant polycarbonate with self-extinguishing fire properties. Coloured options available.

Installation

- Wall or Ceiling Mount.
- Unique first fit polycarbonate base with snap fit gear tray.
- BESA fixing and rear cable entry. 3 way mains terminal block. 4 way terminal block for emergency versions.
- Quick fit clip on diffuser.
- Fast fit Twist-Lock fascia (with single retaining screw).

Standards

- IP54.
- 'F' Mark.
- CE.
- BS EN 60598.

Diffuser Option

Fresnel

Change code

CE(3 or 4)/_K

Options

LED	Centro Circo Code	Colour Finish	Diffuser	IP Rating	CRI	CCT	System Power	Delivered Lumens	Efficacy	Emergency	e-Motion Corridor	Microwave	Dimmable	Night Light	Self Test	Daylight Monitoring
LED	1800	CE3/WL4LED1800	White	Premium Opal	IP54	80	4000K	16.7W	1635lm	97.9lm/W	✓	✓	✓	✓		✓
CFL	Centro Circo Code	Colour Finish	Diffuser	IP Rating	Emergency	e-Motion Corridor	Microwave	Dimmable	Night Light	Self Test	Daylight Monitoring					
B22 GLS	CE3/WL100	White	Premium Opal	IP54												
21W HF	CE3/WL521E	White	Premium Opal	IP54												
28W HF	CE3/WL528E	White	Premium Opal	IP54	✓	✓	✓		✓	✓						
38W HF	CE3/WL538E	White	Premium Opal	IP54			✓									
LED	Centro Circo Maxi Code	Colour Finish	Diffuser	IP Rating	CRI	CCT	System Power	Delivered Lumens	Efficacy	Emergency	e-Motion Corridor	Microwave	Dimmable	Night Light	Self Test	Daylight Monitoring
LED	3000	CE4/WL4LED3000	White	Premium Opal	IP54	80	4000K	21.6W	2335lm	108lm/W	✓	✓	✓	✓		
LED	4000	CE4/WL4LED4000	White	Premium Opal	IP54	80	4000K	32.7W	3390lm	103lm/W	✓	✓	✓	✓		
CFL	Centro Circo Maxi Code	Colour Finish	Diffuser	IP Rating	Emergency	e-Motion Corridor	Microwave	Dimmable	Night Light	Self Test	Daylight Monitoring					
38W HF	CE4/WL538E	White	Premium Opal	IP54	✓	✓	✓	✓		✓						

Code Options (Add suffix to code)



3 Hour Maintained
Emergency
M



Microwave
On/Off
-9



eMotion™ Microwave
Master Dim
-CFP



eMotion™ Microwave
Slave Dim
-CFS



DAYLIGHT Monitoring
-CFDP



Switch Dim
-DD



Night Light
-C7E

Self Test Emergency

Prefix	CE(3 or 4) ST/	Suffix	M
--------	-----------------------	--------	----------

Halo Options	Change / Add to code
--------------	----------------------

White Halo	CH(3 or 4)/__ K
------------	------------------------

Red Halo	CH(3 or 4)/__ R
----------	------------------------

Blue Halo	CH(3 or 4)/__ U
-----------	------------------------